



**Small room fan - Small-room ventilator surface mounted
ECA 100 ipro**



Maico
ECA 100 ipro
0084.0200
4012799842002 EAN/GTIN

78,08 GBP excl. VAT**
plus shipping



3-5 days* (GBR)

Small room fan ECA 100 ipro, mains frequency 50Hz, rated voltage 230V, mounting type surface-mounted, housing material plastic, color white, volume flow 92m³/h, protection class (IP) IPX5, nominal width 100mm, standard composition, axial version, ventilation direction, standard version: on/off via Light switch or separate switch. Operation in either level 1 or level 2. Can be operated in two levels using a commercially available double-toggle switch. Speed controllable. Intelligently programmed small room fan for the highest demands. 2 power levels. Concealed suction through design cover. For ventilation. VDE-GS mark, exception: ECA 100 ipro RC/RCH. VDE mark: ECA 100 RC/RCH. Protection class IP X5 for safety in the bathroom. Protection class II. Suitable for continuous operation. Thermal overload protection. Color traffic white similar to RAL 9016. Housing made of impact-resistant plastic. Motor: Energy-saving, robust motor with ball bearings, maintenance-free. Suitable for continuous operation. Assembly instructions: Very easy to assemble as the cover can be easily removed with tools. Wall and ceiling mounting possible. Compatible with ECA predecessor models DN 100, as mounting holes and cable entry are flush-mounted in the same place. Electrical connection: Flush-mounted electrical connection. Safety instructions: All ECA 100 ipro devices can be used in protection area 1 according to DIN VDE 0100-701. For details see planning information. Article: ECA 100 ipro, version: standard version, delivery volume: 78 m³/h / 92 m³/h, speed: 2100 1/min / 2500 1/min, speed controllable: yes, reversibility: no, SEC average: -10.69 kWh / (m²*a), voltage type: alternating current, rated voltage: 230 V, mains frequency: 50 Hz, nominal power: 6 W / 8 W, IMax: 0.06 A, protection class: IP X5, mains cable: 3/5 x 1.5 mm², installation location: ceiling / wall, installation type: surface-mounted, installation position: any, material: plastic, color: traffic white, similar to RAL 9016, weight: 0.7 kg, flap: none, nominal width: 100 mm, width: 159 mm, height: 159 mm, depth: 130 mm, conveyor temperature at IMax: 40 °C, sound pressure level: 27 dB(A) / 32 dB(A) / distance 3 m, free field conditions

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

