

×

https://www.eibabo.uk/performance-in-light/led-pendant-lamp-4000k-dali-pendant-luminaire-led-not-exc hangeable-8629461786410-eb12005898

LED pendant lamp 4000K DALI - Pendant luminaire LED not exchangeable 8629461786410

Performance in Light 8629461786410 4052075184457 EAN/GTIN

205,77 GBP excl. VAT**

plus shipping bulky item



LED pendant lamp 4000K DALI 8629461786410 Suitable for VDU workstations according to EN 12464-1, LED illuminant cannot be replaced, With illuminant, Suitable for number of illuminants 1, Other socket, Housing material steel, Housing color white, Cover material structured plastic, Design of the grid without, Type of voltage AC /DC, Nominal voltage 220 ... 240V, Nominal LED current at constant current 1800 ... 1800mA, Control gear LED control gear, current-controlled, With control gear, DALI dimming, Programmable dimming, Touch and Dim dimming, Dimming with push-button, Other light distributors, Reflector without, symmetrical light distribution, direct/indirect light emission, energy efficiency index (EEI) of the power supply A1, rated service life L70/B10 at 25 °C 75000h, rated service life L90/B50 be i 25 °C 33300h, Degree of protection (IP) IP20, Degree of protection (NEMA) 1, Impact resistance IKO5, Protection class I, Suitable for emergency lighting, Glow wire test according to IEC 60695-2-11 650 °C - 30 s, Suitable for lamp power 62 ... 62W, max. system power 69W, rated luminous flux according to IEC 62722-2-1 8410lm, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, power factor 0.89, width 273mm, height/depth 29mm, length 1544mm, suspension included, pendant length 300 ... 1500mm, type of wiring suitable for through-wiring, number of poles 5, conductor cross-section 1.5mm², connection type plug-in terminal, pendant light SL629 with high-performance LED. Lamp power 69W. universally usable linear luminaire for the office area. clear design language and restrained optics support a harmonious integration into the existing architecture. Particularly suitable for lange office and educational facilities due to easy maintenance, great technical variability and a balanced price-performance ratio. Luminaire housing made of sheet steel. Light engine can be replaced by means of a slide-in mechanism. Scratch-resistant surface design hanks to high-quality powder coating according to

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online



