



Window air conditioner monobl., cooling 1.3.65kW AK36M AirBlue



Swegon
AK36M AirBlue
2596251
4250059911277 EAN/GTIN

972,06 GBP excl. VAT**
plus shipping bulky item



14-16 days* (GBR)

Window air conditioner monobloc., cooling 1.3.65kW AK36M AirBlue operating principle only cooling, operation remote control, absorbed cooling capacity 1.03 ... 1.3kW, cooling capacity 3.65 ... 3.65kW, max. air volume 480m³/h, dehumidification capacity 1.6l/h, type of refrigerant other, energy efficiency class cooling A, annual energy consumption cooling (550 hours - full load) 567kWh, EER (cooling) 3.54, height 428mm, width 660mm, depth 700mm, connection voltage (system) 230V, fuse (slow) 16A, operating temperature cooling (dry bulb) 16 ... 30°C, sound pressure level (cooling) 46 ... 50dB(A), energy efficiency class spectrum A+ to F, monoblock air conditioner, with this service-friendly window air conditioner, unwanted temperatures are gone very quickly from the window. A pull-out chassis provides very easy access to all components. The housing is made of galvanized sheet steel with a weather-resistant finish, the attractive plastic front panel with integrated air filter blends inconspicuously into any room. In addition to pure cooling operation, the device can also be used for dehumidification and ventilation. The electronic control can be done either by direct operation on the device or alternatively by the standard infrared remote control. Refrigerant R32, inverter technology, 3 fan speeds, automatic function, IR remote control, timer function, service-friendly with extendable chassis, attractive front panel made of plastic, Auto Swing horizontal, filter notification for cleaning, room size up to 24 m², nominal cooling power consumption 1.30 kW, power consumption at 235 h/a 240 kWh/a, SEER cooling 5.40, air volume flow inside N/M/H cooling 380/430/480 m³/h, air volume flow outside cooling 1200 m³/h, sound power level inside N/M/H cooling 55 /57/59 dB(A), sound pressure level inside N/M/H 46/48/50 dB(A), sound power level outside N/M/H cooling 61/63/65 dB(A), sound pressure level outside N/M/H cooling 54/56/58 dB(A), refrigerant R32, GWP 675 kgCO2eq., refrigerant content 0.63 kg, power supply 230/1/50 V/~Hz, weight 50.0 kg, operating range outside temperature cooling 16°C up to 43°C.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

