×



Item Number EB11104817

https://www.eibabo.uk/warema/motor-control-unit-2-reg-4-te-electronic-motor-control-device-2016481-eb11104817



Motor control unit 2 REG, 4 TE - Electronic motor control device 2016481

Warema

2016481 4251317204148 EAN/GTIN

121,24 GBP excl. VAT**

plus **shipping**



14-16 days* (GBR)

Motor control unit 2 REG, 4 TE 2016481 Rated operational current le 0.0016 ... 0.0016A, Rated operational voltage Ue at AC 50 Hz 207 ... 253V, Rated operational frequency 50 ... 50Hz, Type of connection technology screw connection, Rated control supply voltage Us at DC 36 ... 36V, type of voltage for actuation DC, number of outputs, contact-based 4, number of binary inputs 6, monostable switching function, design of electrical connection for auxiliary and control circuit screw connection, degree of protection (IP) IP30, motor control unit (MSE) for the control of 2 motors via the sun protection control center. Two drives can be connected to the motor control unit at the same time. A separate button can also be connected for each motor output for local operation. The engine control unit is operated via separate control and power conductor lines. The safety extra-low voltage is generated in the engine control unit itself. An external power pack is not necessary. Different programs can be set for sun protection products with and without slats. A local move command is saved after 2 seconds or immediately, depending on the programming. With a central command, this drive command is deleted and local operation is blocked. In order to be able to ensure continuity, a separate input for connecting a locking contact, e.g. B. window contact available. All connection terminals are designed as screw terminals for safe installation. The logic behavior, timer logic or permanent logic, can be switched on the device using a coding switch. In addition, the housing is halogen-free and complies with the UL-94 V0 test. The housing corresponds to the standard for built-in devices according to DIN 43880. There is a replaceable fine-wire fuse for protecting the motor cable for the motor output. The engine control unit has a size of 4TE.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®




COMPLAINTS HANDLING Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION





25 YEARS OF EXPERIENCE In worldwide mail order





DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

