



## Fan 150mm, automatic - Window ventilator 240m³/h 150mm EVN 15



**Maico**  
**EVN 15**  
0080.0853  
4012799808534 EAN/GTIN

**177,90 GBP** excl. VAT\*\*  
plus shipping



3-5 days\* (GBR)

Fan 150mm, automatic EVN 15, mains frequency 50Hz, rated voltage 230V, conveyor temperature -20... 40°C, housing material plastic, color white, volume flow 240m³/h, speed 15501/min, protection class (IP) IP24, ventilation version, nominal width 150mm, automatic closing flap, protective grille on the suction side, yellow chromated, contact protection in accordance with DIN EN ISO 13857. 8-blade impellers made of glass fiber reinforced polyamide. Dynamically balanced in 2 levels, in accordance with quality level 6.3, DIN ISO 1940, Part 1. Installation possible in any position. Conveying direction: The following figure shows the conveying direction: Conveying direction A: Suction via the motor, standard. Conveying direction B: Blowing via the motor, on request. Direction of rotation, reversing operation: The volume flow decreases by approx. 35% if the conveying direction is abnormal. Motor: asynchronous motor. Speed controllable. Exception: Type EZQ 45/6 B, EZS 45/6 B, DZQ 40/2 B and DZS 40/2 B. Reversible. Exception: Fans with shaded-pole motors (...-E). Not suitable for pumping air saturated with water vapor. AC motor: EZQ and EZS series. Rated voltage 230 V, 50 Hz. Thermal overload protection as standard. Fans.. /B: Capacitor motors with operating capacitor on the protective grille or on the wall sleeve, protection class IP 55. Fans.. /D: Capacitor motors with operating capacitor in the connection box, protection class IP 54. Fans.. /E: Shaded pole motors, non-reversible, protection class IP 54. Electrical connection: To the terminal strip in the end cover of the motor. Safety instructions: The fan may only be put into operation if contact protection of the impeller is guaranteed in accordance with DIN EN ISO 13857. Article: EZQ 30/2 B, version: square wall plate, delivery volume: 3620 m³/h, nominal delivery volume: 2700 m³/h / in opt. Efficiency, pressure pfs, nominal: 170 Pa - in opt. Efficiency, speed nominal: 2840 1/min - in opt. Efficiency, speed: 2881 1/min, impeller type: axial, speed controllable: yes, reversibility: yes, voltage type: alternating current, rated voltage: 230 V, mains frequency: 50 Hz, nominal power: 350 W / in opt. Efficiency, Irated: 1.6 A / in opt. Efficiency, IMax: 2.7 A, protection class: IP 55, thermal class: B, installation location: wall / ceiling, installation type: surface-mounted, installation position: horizontal / vertical, material: sheet steel, galvanized, weight: 11.7 kg, nominal width: 300 mm, width: 465 mm, height: 465 mm, depth: 270 mm, conveyor temperature at nominal current: -20 °C to 80 °C, conveyor temperature at IMax: -20 °C to 40 °C, overall efficiency e:...

### YOUR ADVANTAGES



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

