4-fold security terminal - KNX sensor control MT/S 4.12.2M

ABB
MT/S 4.12.2M
2CDG110109R0011
4016779711876 EAN/GTIN

124,57 GBP excl. VAT**
plus **shipping**

🚚 14-16 days* (GBR)

Security terminal 4-fold REG MT/S 4.12.2M bus system KNX, other bus systems without, version detector group terminal, type of installation REG, number of inputs 4, protection class (IP) IP20, is used as an interface between sensors of the security technology and the KNX. The device has inputs, so-called detector groups. They are used for the monitored connection of passive detectors (e.g. magnetic contacts and/or glass breakage sensors) to the ABB i-bus® KNX or for the connection of potential-free contacts in applications with increased security requirements. There are 3 relay contacts available for direct control of the signaling devices or reporting of status information. The security terminal can be used as a system with independent alarm logic or in combination with the security module SCM/S or an intruder alarm control panel (GM/A 8.1 or L240 with KNX interface XS/S). The device requires an external 12 V DC SELV auxiliary voltage (e.g. NTU/S 12.2000.1).

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

DHL TRACK & TRACE
Shipment tracking

COMPLAINTS HANDLING
Obliging and 100% safely

25 YEARS OF EXPERIENCE
In worldwide mail order

ORDER LIVE CHAT
With order history

SHORT DELIVERY TIME
Warehousing

REFUND
Within 14 days

DATA PROTECTION
Guarantee

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online