

Item Number EB14201436

https://www.eibabo.uk/vaillant/pressure-resistant-hot-water-tank-boiler-electric-veh-80-7-pro-eb142014



Pressure-resistant hot water tank - Boiler electric VEH 80/7 pro

×

Vaillant

VEH 80/7 pro 0010016658 4024074755822 EAN/GTIN

435,73 GBP excl. VAT**

plus shipping bulky item



3-5 days* (GBR)

Pressure-resistant hot water tank VEH 80/7 per energy efficiency class C, energy efficiency class spectrum A+ to F, boiler material steel, jacket material steel, volume of the tank 80l, nominal output 6kW, connection voltage 230 ... 400V, three-phase version, frequency 50 Hz, hanging version, With off-peak mode, can be used with normal water pressure, connection to a hot water pipe, warm-up time from 10 °C - 65 °C 45 min, tapping capacity at 60 °C, continuous operation 20 l/min, vertical placement, temperature limitation, max. permissible operating pressure 6 bar, with cleaning opening, protective anode, Height 916mm, width 504mm, depth 450mm, diameter 504mm, cold drinking water connection male thread, nominal inside diameter cold drinking water 1/2 inch (15), hot water connection male thread, nominal inside diameter to twater connection 1/2 inch (15), protection class (IP) IP25, tapping profile M, VEH 80/7 per electric hot water tank closed system, wall-mounted Product advantages - Minimum stand-by energy consumption loss due to highly efficient thermal insulation - rapid heating for additional hot water requirements - anti-scald protection that can be activated - anti-freeze function - connected load adjustable by moving bridges Equipment - universal heating flange for single-circuit, dual-circuit and boiler operation - temperature controller infinitely adjustable from 7 to 85 degrees C - high-quality storage enamelling and stainless steel radiators with long Service life - Protection against water jets IP25 enables unrestricted installation in protection area I - Integrated ball valve for quick emptying Nominal capacity 80 I Permissible operating pressure 6 bar Standby heat loss at 65 °C (24 h) 0.92 kWh Mixed water volume at 40 °C 157 I cold/ Hot water connection R 1/2 Height/width/depth 916/504/450 mm Weight unpacked 50 kg Weight ready for operation 130 kg Seasonal hot water preparation

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

