Item Number
EB13701809

28.03.2024/16:33

https://www.eibabo.uk/siemens/circuit-breaker-icu-55ka-ir-10-25a-3va2125-5kp32-0aa0-eb13701809



Circuit breaker ICU=55kA IR=10-25A 3VA2125-5KP32-0AA0

Siemens
3VA2125-5KP32-0AA0
4042948801833 EAN/GTIN

751,54 GBP excl. VAT**

plus **shipping**

14-16 days* (GBR)

Circuit breaker ICU=55kA IR=10-25A 3VA2125-5KP32-0AA0 Rated uninterrupted current Iu 25A, rated voltage 690 ... 690V, rated limiting short-circuit breaking current Icu at 400 V, 50 Hz 55kA, overload release current setting 10 ... 25A, setting range of the short-time delayed short-circuit release 15 .. 250A, setting range of the instantaneous short-circuit release 38 ... 300A, connection type main circuit screw connection, device design built-in device fixed installation technology, suitable for DIN rail mounting, DIN rail mounting optional, number of auxiliary contacts as NC contact 0, number of auxiliary contacts as NO contact 0, number of auxiliary contacts as changeover contact 0, number of poles 3, position of the connection for the main circuit at the front, design of the toggle lever actuating element, complete device with protective unit, optional motor drive, degree of protection (IP) IP40, circuit breaker 3VA2 IEC Frame 160 switching capacity class M Icu=55kA @ 415V 3-pole, system protection ETU850, LSI, In= 25A overload protection Ir=10A...25A short-circuit protection Isd=0.6..10x In, Ii=1.5..12x In N conductor protection optionally with external current transformer, up to 160% flat screw terminal 3VA2 molded case circuit breakers with ETU, 8 series for system protection. The 3VA molded case circuit breakers from Siemens, as an important part of the SENTRON protective components for industrial applications and for applications in the infrastructure sector, offer effective starter and motor protection for systems through safe shutdown in the event of overload and short circuits. The 3VA molded case circuit breakers set standards in terms of flexibility and modular variety of accessories. Uniform accessories for several sizes across all series of 3VA1 and 3VA2 molded case circuit breakers. This variant of the 3VA molded case circuit breaker is primarily characterized by: 1. Compact design. 2. Available as a variant for system protection and generator protection. 3. Available in 3 and 4 pole versions. 4. Four switching capacity classes from 55 kA ... 150 kA at 415 V. 5. Depending on the size: Rated current 25 A.630 A. 6. Can be installed in fixed, plug-in or slide-in technology. 7. The series has an electronic overcurrent release. 8. Has an integrated display for showing the measured values. 9. Integrated measuring function and optional communication connection via Modbus TCP, Modbus RTU, PROFINET and PROFIBUS. 10. Modular and easy to assemble internal accessories with multiple functions. For the safe, efficient electrical infrastructure in buildings and industry, Siemens offers an integrated...

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

DHL TRACK & TRACE
Shipment tracking

COMPLAINTS HANDLING
Obliging and 100% safely

25 YEARS OF EXPERIENCE
In worldwide mail order

ORDER LIVE CHAT
With order history

SHORT DELIVERY TIME
Warehousing

REFUND
Within 14 days

DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).
** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online