

Item Number EB13701594

https://www.eibabo.uk/siemens/circuit-breaker-icu-110ka-in-63a-3va2063-7hl36-0aa0-eb13701594



Circuit breaker ICU=110kA IN=63A 3VA2063-7HL36-0AA0

×

Siemens

3VA2063-7HL36-0AA0 4042948833476 EAN/GTIN

457,22 GBP excl. VAT**

plus **shipping**



14-16 days* (GBR)

Circuit breaker ICU=110kA IN=63A 3VA2063-7HL36-0AA0 Rated uninterrupted current lu 63A, rated voltage 690 ... 690V, rated limiting short-circuit breaking current lcu at 400 V, 50 Hz 110kA, overload release current setting 25 ... 63A, setting range of the instantaneous short-circuit release 95 ... 756A, connection type main circuit box terminal, device design built-in device, suitable for top hat rail mounting, top hat rail mounting optional, number of auxiliary contacts as opener 0, number of auxiliary contacts as changeover contact 0, number of poles 3, position of the connection for the main circuit at the front, design of the actuating element Toggle lever, complete device with protection unit, optional motor drive, degree of protection (IP) IP40, circuit breaker 3VA2 IEC Frame 100 switching capacity class C Icu=110kA @ 415V 3-pole, system protection ETU320, LI, In=63A overload protection Ir=25A...63A short-circuit protection Ii= 1.5...12 x In terminal connection 3VA2 molded case circuit breakers with ETU 8-way re ihe for system protection. The 3VA molded case circuit breakers from Siemens, as an important part of the SENTRON protective components for industrial applications and for applications in the infrastructure sector, offer effective starter and motor protection for systems through safe shutdown in the event of overload and short circuits. The 3VA molded case circuit breakers set standards in terms of flexibility and modular variety of accessories. Uniform accessories for several sizes across all series of 3VA1 and 3VA2 molded case circuit breakers. This variant of the 3VA molded case circuit breaker is primarily characterized by: 1. Compact design. 2. Available as a variant for system protection and generator protection. 3. Available in 3 and 4 pole versions. 4. Four switching capacity classes from 55 kA ... 150 kA at 415 V. 5. Depending on the size: Rated current 25 A.630 A. 6. Can be installed in fixed, plug-in or slide-in technology. 7. The series has an electronic overcurrent release. 8. Has an i

YOUR ADVANTAGES



WORLDWIDE TRADECorporate video eibmarkt®



COMPLAINTS HANDLING
Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE *In worldwide mail order*



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTIONGuarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

