



Contactor 18, 5kW/400V, 2NO+2NC - Magnet contactor 41A 20...33VAC 3RT2035-3NB34-3MA0



Siemens
3RT2035-3NB34-3MA0
 4011209942196 EAN/GTIN

156,03 GBP excl. VAT**
 plus shipping



14-16 days* (GBR)

Contactor 18.5kW/400V, 2NO+2NC 3RT2035-3NB34-3MA0 Rated control supply voltage Us at AC 50 Hz 20 ... 33V, Rated control supply voltage Us at AC 60 Hz 20 ... 33V, Rated control supply voltage Us at DC 20 ... 33V, voltage type for actuation AC/DC, rated operational current Ie at AC-1, 400 V 60A, rated operational current Ie at AC-3, 400 V 41A, rated operational power at AC-3, 400 V 18.5kW, rated operational current Ie at AC-4, 400 V 35A, Rated operational power at AC-4, 400 V 18.5kW, Rated operational power NEMA 22.0649625kW, Suitable for series installation, Number of auxiliary contacts as NO contact 2, Number of auxiliary contacts as NC contact 2, Connection type main circuit screw connection, Number of NC contacts as main contacts 0, Number of NO contact as main contacts 3, power contactor, AC-3 40 A, 18.5 kW / 400 V 2 NO + 2 NC, AC / DC 20-33 V, communication-capable, with varistor, 3-pole, size S2, spring-loaded connection, Auxiliary switch cannot be removed SIRIUS 3RT2 power contactor for switching Motor. The 3RT2 contactors are part of the SIRIUS modular system with its perfectly matched products. They impress with their high performance combined with a compact design and high contact reliability. They can be combined with other components in the load feeder in a variety of ways. Many of the device combinations are tested at the factory. The contactors offer the optimal connection to the controller for every application (parallel, via ASI or IO-Link). Integrated auxiliary switches reduce the complexity of your structure. The front connections enable easy wiring. The 3RT2 contactors are climate-proof, approved worldwide (eg IEC and UL/CSA) and IE3/IE4ready. They are available in various sizes and in a large power range with AC and DC operation. In addition to screw connection technology, the devices are also consistently available with spring-loaded connections for a fast, maintenance-free and vibration-proof connection. The comprehensive range of accessories, such as auxiliary switches, auxiliary releases, etc. is the same for all sizes. The available link modules, function modules and the SIRIUS 3RV29 infeed system significantly reduce the wiring effort. The 3RT2 power contactors replace the proven 3RT1 series (up to 55 kW). Simple, efficient, always up-to-date - the SIRIUS modular system.

YOUR ADVANTAGES



WORLDWIDE TRADE
 Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
 > 500,000 customers worldwide



DHL TRACK & TRACE
 Shipment tracking



COMPLAINTS HANDLING
 Obliging and 100% safely



25 YEARS OF EXPERIENCE
 In worldwide mail order



ORDER LIVE CHAT
 With order history



SHORT DELIVERY TIME
 Warehousing



REFUND
 Within 14 days



DATA PROTECTION
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
 eibabo® electronics cheap online order
 eibabo® electric appliances buy online

