eibabo technology store

**Item Number**
**EB12904036**

**28.03.2024/09:31**

https://www.eibabo.uk/siemens/indicator-light-22mm-round-red-3su1156-6aa20-3aa0-eb12904036



## Indicator light 22mm, round, red 3SU1156-6AA20-3AA0

**Siemens**
3SU1156-6AA20-3AA0
4011209967328 EAN/GTIN

**16,48 GBP** excl. VAT**
plus **shipping**

14-16 days* (GBR)

Indicator light 22mm, round, red 3SU1156-6AA20-3AA0 Number of indicator lights 1, color of the lens other, design of the socket other, with lamp, rated operating voltage Ue 230 ... 230V, type of voltage AC, design of the electrical connection spring-loaded connection, design of the lens round , Design of the lens flat, hole diameter 22.3mm, width of the opening 29.5mm, height of the opening 11.8mm, material of the front ring other, color of the front ring other, protection class (IP) IP67/IP69K, protection class (NEMA) 13, indicator light, 22 mm, round, metal, high-gloss, red, lens, smooth, with holder, LED module with integrated LED AC 230 V, spring-loaded connection SIRIUS ACT indicator light for signaling switching statuses or faults in systems with brilliant luminosity thanks to energy-efficient LED technology. Under the brand name SIRIUS ACT, Siemens offers a unique portfolio of commanding and signaling devices with global product approvals in four modern design series made of robust real metal and high-quality plastic. The innovative snap-on concept simplifies assembly to such an extent that only one hand and no special tools are required. Groove-free holes are sufficient as mounting holes, as 100% anti-twist protection is already integrated. Thanks to the consistently high degree of protection, the robust devices are suitable for industrial use and outdoor use. Even cleaning with a high-pressure jet is possible. Neither dust, oil nor aggressive alkalis can interfere with reliable operation. In addition to the standard wiring, the devices can also be connected to the controller via PROFINET, AS-Interface or IO-Link. This reduces your wiring effort, minimizes sources of error and gives you more flexibility. The graphic online configurator provides convenient support when selecting and ordering individual devices, housings and labels. Extensive documentation (e.g. manual, 3D data, connection diagram) is available. Available versions: several colors, different voltage variants. Note: Complete device, delivery including holder and modules. SIRIUS ACT - Performance in Action when commanding and reporting. Simply assembled, simply strong, simply perfect.

### YOUR ADVANTAGES

**WORLDWIDE TRADE**
*Corporate video eibmarkt®*

**99% CUSTOMER SATISFACTION**
*> 500,000 customers worldwide*

**DHL TRACK & TRACE**
*Shipment tracking*

**COMPLAINTS HANDLING**
*Obliging and 100% safely*

**25 YEARS OF EXPERIENCE**
*In worldwide mail order*

**ORDER LIVE CHAT**
*With order history*

**SHORT DELIVERY TIME**
*Warehousing*

**REFUND**
*Within 14 days*

**DATA PROTECTION**
*Guarantee*

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

**eibabo®** and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).
** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

**eibabo®** the Smart Home technology shop
**eibabo®** electronics cheap online order
**eibabo®** electric appliances buy online