



## Contactor 22kW/400V, 1NO+1NC - Magnet contactor 51A 230VAC 3RT2036-1AL20-1AA0



**Siemens**  
**3RT2036-1AL20-1AA0**  
 4011209940079 EAN/GTIN

**133,63 GBP** excl. VAT\*\*  
 plus shipping



14-16 days\* (GBR)

Contactor 22kW/400V, 1NO+1NC 3RT2036-1AL20-1AA0 Rated control supply voltage  $U_s$  at AC 50 Hz 230 ... 230V, rated control supply voltage  $U_s$  at AC 60 Hz 230 ... 230V, type of voltage for actuation AC, rated operational current  $I_e$  at AC-1, 400 V 70A, rated operational current  $I_e$  at AC-3, 400 V 51A, rated operational power at AC-3, 400 V 22kW, rated operational current  $I_e$  at AC-4, 400 V 41A, rated operational power at AC-4, 400 V 22kW, rated operational power NEMA 29.41995kW, Suitable for series installation, number of auxiliary contacts as NO contact 1, number of auxiliary contacts as NC contact 1, connection type main circuit screw connection, number of NC contacts as main contacts 0, number of NO contacts as main contacts 3, power contactor, AC-3 50 A, 22 kW / 400 V 1 NO + 1 NC, AC 230 V 50/60 Hz, 3-pole, size S2, screw connection upright mounting position SIRIUS 3RT2 power contactor for switching motors. The 3RT2 contactors are part of the SIRIUS modular system with its optimally matched mmed products. They impress with their high performance combined with a compact design and high contact reliability. They can be combined with other components in the load feeder in a variety of ways. Many of the device combinations are tested at the factory. The contactors offer the optimal connection to the controller for every application (parallel, via ASi or IO-Link). Integrated auxiliary switches reduce the complexity of your structure. The front connections enable easy wiring. The 3RT2 contactors are climate-proof, approved worldwide (eg IEC and UL/CSA) and IE3/IE4ready. They are available in different sizes and in a large power range with AC and DC operation. In addition to screw connection technology, the devices are also consistently available with spring-loaded connections for a fast, maintenance-free and vibration-proof connection. The comprehensive range of accessories, such as auxiliary switches, auxiliary releases, etc., is the same for all sizes. The available link modules, function modules and the SIRIUS 3RV29 infeed system significantly reduce the amount of wiring. The 3RT2 power contactors replace the tried-and-tested 3RT1 series (up to 55 kW). Simple, efficient, always up-to-date - the SIRIUS modular system.

### YOUR ADVANTAGES



**WORLDWIDE TRADE**  
 Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
 > 500,000 customers worldwide



**DHL TRACK & TRACE**  
 Shipment tracking



**COMPLAINTS HANDLING**  
 Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
 In worldwide mail order



**ORDER LIVE CHAT**  
 With order history



**SHORT DELIVERY TIME**  
 Warehousing



**REFUND**  
 Within 14 days



**DATA PROTECTION**  
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
 eibabo® electronics cheap online order  
 eibabo® electric appliances buy online

