



## Motor protection circuit-breaker 25A 3RV2131-4DA10


**Siemens**

3RV2131-4DA10

4011209930544 EAN/GTIN

**144,21 GBP** excl. VAT\*\*  
plus shipping



14-16 days\* (GBR)

Circuit breaker 25A 3RV2131-4DA10 overload release current setting 18 ... 25A, setting range of the instantaneous short-circuit release 325 ... 325A, with thermal protection, sensitive to phase failure, magnetic tripping technology, rated operational voltage 690 ... 690V, rated uninterrupted current I<sub>u</sub> 25A, rated operational power at AC-3, 230 V 5.5kW, rated operational power at AC-3, 400 V 11kW, connection type main circuit screw connection, design of the actuating element rotary knob, device type built-in device fixed installation technology, number of poles 3, rated limiting short-circuit breaking current I<sub>cu</sub> at 400 V, AC 65kA, protection class (IP) IP20, height 140mm, width 75mm, depth 149mm, circuit breaker size S2 for motor protection, CLASS 10 with overload relay function A release 18...25 A N release 325 A screw connection, standard switching capacity SIRIUS 3RV2 circuit breaker for motor protection with overload relay function for safe disconnection in the event of a short circuit and consumer protection and system against overload, as well as for safe disconnection of the system from the mains. The compact and climate-proof circuit breakers are optimized for use in consumer feeders due to their low waste heat, of course also for IE3/IE4 motors and equally for switching direct current. Worldwide approvals (e.g. IEC and UL/CSA) and use in potentially explosive applications (ATEX or IEC Ex) are a matter of course. Device variants are available for motor protection (also with overload relay function), system protection, short-circuit protection of starter combinations, transformer protection, as main and EMERGENCY STOP switches and for use in IT networks. They are available with a screw or spring-loaded connection for a fast, maintenance-free and vibration-proof connection, and optionally with a built-in auxiliary switch. The comprehensive range of accessories, such as auxiliary switches, auxiliary releases, signaling switches, etc., is the same for all sizes. The use of various power supply options, such as the associated SIRIUS 3RV2 infeed system, reduces the main circuit wiring considerably. The 3RV2 circuit breakers replace the tried-and-tested 3RV1 series. Simple, efficient, always up-to-date - the SIRIUS modular system.

### YOUR ADVANTAGES


**WORLDWIDE TRADE**

Corporate video eibmarkt®


**COMPLAINTS HANDLING**

Obliging and 100% safely


**SHORT DELIVERY TIME**

Warehousing


**99% CUSTOMER SATISFACTION**

&gt; 500,000 customers worldwide


**25 YEARS OF EXPERIENCE**

In worldwide mail order


**REFUND**

Within 14 days


**DHL TRACK & TRACE**

Shipment tracking


**ORDER LIVE CHAT**

With order history


**DATA PROTECTION**

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

