



Motor protection circuit-breaker 25A 3RV2332-4DC10


Siemens

3RV2332-4DC10

4011209944640 EAN/GTIN

159,15 GBP excl. VAT**
plus shipping



14-16 days* (GBR)

Circuit breaker rated current 25A 3RV2332-4DC10 Setting range of the instantaneous short-circuit release 325 ... 325A, magnetic release technology, rated operating voltage 690 ... 690V, rated uninterrupted current Iu 25A, rated operational power at AC-3, 230 V 5.5kW, rated operational power at AC-3, 400 V 11kW, connection type main circuit screw connection, version of the actuating element rotary knob, device type built-in device fixed installation, number of poles 3, rated breaking short-circuit current Icu at 400 V, AC 100kA, degree of protection (IP) IP20, height 140mm, width 55mm, depth 149mm, circuit breaker size S2 for starter combination rated current 25 A N release 325 A screw connection increased switching capacity SIRIUS 3RV2 circuit breakers for starter combinations for reliable protection of loads in the event of a short circuit and for safe disconnection from the network. The compact and climate-proof circuit breakers are optimized for use in load feeders thanks to their low waste heat, n Of course also for IE3/IE4 motors and equally for switching direct current. Worldwide approvals (e.g. IEC and UL/CSA) and use in potentially explosive applications (ATEX or IEC Ex) are a matter of course. Device variants are available for motor protection (also with overload relay function), system protection, short-circuit protection of starter combinations, transformer protection, as main and EMERGENCY OFF switches and for use in IT networks. They are available with a screw or spring-loaded connection for a fast, maintenance-free and vibration-proof connection, and optionally with a built-in auxiliary switch. The comprehensive range of accessories, such as auxiliary switches, auxiliary releases, signaling switches, etc., is the same for all sizes. The use of various power supply options, such as the associated SIRIUS 3RV29 infeed system, reduces the main circuit wiring considerably. The 3RV2 circuit breakers replace the tried-and-tested 3RV1 series. Simple, efficient, always up-to-date - the SIRIUS modular system.

YOUR ADVANTAGES


WORLDWIDE TRADE

Corporate video eibmarkt®


99% CUSTOMER SATISFACTION

> 500,000 customers worldwide


DHL TRACK & TRACE

Shipment tracking


COMPLAINTS HANDLING

Obliging and 100% safely


25 YEARS OF EXPERIENCE

In worldwide mail order


ORDER LIVE CHAT

With order history


SHORT DELIVERY TIME

Warehousing


REFUND

Within 14 days


DATA PROTECTION

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

