



**LED recessed ceiling light Q68 10W827230VFLSMWH -  
Downlight/spot/floodlight PANOS EVO #60815078**



**Zumtobel**  
PANOS EVO #60815078  
60815078  
4053167129608 EAN/GTIN

**142,51 GBP** excl. VAT\*\*  
plus shipping



14-16 days\* (GBR)



LED recessed ceiling light Q68 10W827230VFLSMWH PANOS EVO 60815078 Suitable for recessed mounting, Suitable for ceiling mounting, Adjustability not adjustable, Light source LED not replaceable, With light source, Suitable for number of light sources 1, Socket without, Housing material aluminium, Housing color white, Cover material opal plastic, Type of voltage AC, Rated voltage 220 ... 240V, Control gear LED control gear, current-controlled, With control gear, Without dimming function, Reflector without, Light distribution asymmetrical, Light emission direct, Rated service life L70/B50 at 25 °C 100000h, Rated service life L80/B50 at 25 °C 66000h, rated service life L90/B50 at 25 °C 33000h, degree of protection (IP) IP20, protection class II, max. system power 10W, light color white, color temperature 2700 ... 2700K, color rendering index CRI 80-89, rated luminous flux according to IEC 62722-2-1 660lm, width 78mm, height/depth 77mm, length 78mm, installation width 68mm, installation height/depth 100mm, installation length 68mm, glow wire p Test according to IEC 60695-2-11 850 °C - 30 s, color consistency (MacAdam ellipse) SDCM3, LED recessed ceiling light (complete light), "Stable White", highest quality of light thanks to specially designed reflector, fitted with: 10 W LED827, FLOOD emission characteristics, reflector: smooth, coated in an aluminum color and matt (31 °), color rendering Ra > 80, color temperature 2700 K (warm white), color location tolerance (initial MacAdam): 3, luminous flux of luminaire: 660 lm, luminous efficacy of luminaire: 66 lm /W, service life: 50000h at 85% luminous flux, with ballast unit, modular, high-quality optical unit made of reflector and LED light chamber, integrated in optimized heat management made of die-cast aluminium, reflector/cover frame made of high-quality, UV-resistant polycarbonate (PC), cover frame white, mounting frame made of die-cast aluminium, tool-free rapid assembly of the lighting unit via EASY-CLICK fastener, IP44\_IP20, luminaire wired without halogen, connection: 2-pole terminal, mains voltage: 220-240V / 0/50/60 Hz, suitable for central batteries 220V DC, assembly: tool-free quick assembly using anti-slip retaining springs for ceiling thicknesses of 1-25mm, ceiling cut-out: 68x68mm, installation depth: 100mm, weight: 0.33 kg

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

