



**LED recessed ceiling light R100H 18W827230VWHWH -  
Downlight/spot/floodlight PANOS EVO #60815165**



**Zumtobel**  
PANOS EVO #60815165  
60815165  
4053167130482 EAN/GTIN

**152,34 GBP** excl. VAT\*\*  
plus shipping



14-16 days\* (GBR)

LED recessed ceiling light R100H 18W827230VWHWH PANOS EVO 60815165 Suitable for recessed mounting, Suitable for ceiling mounting, Adjustability not adjustable, Light source LED cannot be replaced, With light source, Suitable for number of light sources 1, Socket without, Housing material aluminium, Housing color white, Cover material opal plastic, Voltage type AC, Nominal voltage 220 ... 240V, LED nominal current at constant current 82 ... 82mA, Control gear LED control gear current-controlled, With control gear, Without dimming function, Reflector without, Light distribution symmetrical, Light emission direct, Rated service life L70/B50 at 25° C 100000h, rated service life L80/B50 at 25 °C 66000h, rated service life L90/B50 at 25 °C 33000h, degree of protection (IP) IP20, impact resistance IK04, protection class II, max. system power 18W, light color white, color temperature 2700 ... 2700K, Color rendering index CRI 80-89, rated luminous flux according to IEC 62722-2-1 1269lm, power factor 0.95, height/depth 123mm, ext diameter 113mm, installation height/depth 140mm, installation diameter 100mm, glow wire test according to IEC 60695-2-11 850 °C - 30 s, color consistency (MacAdam ellipse) SDCM3, LED recessed ceiling light (complete light), "Stable White", Cut-off angle 45°, fitted with: 18 W LED827, color rendering Ra > 80, color temperature 2700 K (warm white), color location tolerance (initial MacAdam): 3, luminous flux of luminaires: 1269 lm, luminous efficacy of luminaires: 70 lm/W, service life: 50000h at 85 % luminous flux, with ballast unit, modular, high-quality optical unit consisting of reflector and LED light chamber, integrated in optimized heat management made of die-cast aluminum, smooth reflector painted white, reflector/cover ring made of high-quality, UV-resistant polycarbonate (PC), cover ring white, mounting ring made of glass-fibre reinforced polycarbonate (PC), grey, tool-free rapid assembly of the luminaire unit using a bayonet catch, IP44\_IP20, luminaire wired without halogen, connection: 3-pin plug-in connection terminal, looping through possible ch, mains voltage: 220-240V / 0/50/60Hz, suitable for central battery 220V DC, assembly: tool-free quick assembly using anti-slip retaining springs for ceiling thicknesses of 1-40mm, ceiling cut-out: 100mm, installation depth: 140mm, weight: 0.52 kg, Note: UGR

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

