



LED recessed ceiling light Q100L 11W830230VSMWH - Downlight/spot/floodlight PANOS EVO #60815194



Zumtobel
PANOS EVO #60815194
60815194
4053167130772 EAN/GTIN

165,45 GBP excl. VAT**
plus shipping

 **14-16 days* (GBR)**



LED recessed ceiling light Q100L 11W830230VSMWH PANOS EVO 60815194 Suitable for recessed mounting, Suitable for ceiling mounting, Adjustability not adjustable, Light source LED cannot be replaced, With light source, Suitable for number of light sources 1, Socket without, Housing material aluminium, Housing color white, Cover material opal plastic, Voltage type AC, Rated voltage 220 ... 240V, LED rated current at constant current 53 ... 53mA, Control gear LED control gear, current-controlled, With control gear, Without dimming function, Reflector without, Light distribution asymmetrical, Light emission direct, Rated service life L70/B50 at 25 ° C 100000h, rated service life L80/B50 at 25 ° C 66000h, rated service life L90/B50 at 25 ° C 33000h, degree of protection (IP) IP20, impact resistance IK04, protection class II, max. system power 11W, light color white, color temperature 3000 ... 3000K, Color rendering index CRI 80-89, rated luminous flux according to IEC 62722-2-1 782lm, power factor 0.9, width 115mm, height/depth 104mm, length 115mm, installation width 100mm, installation height/depth 102mm, installation length 100mm, glow wire test according to IEC 60695-2-11 850 °C - 30 s, color consistency (MacAdam ellipse) SDCM3, LED recessed ceiling light (complete light), " Stable White", cut-off angle 60°, fitted with: 11 W LED830, color rendering Ra > 80, color temperature 3000 K (warm white), color location tolerance (initial MacAdam): 3, luminous flux of luminaires: 782 lm, luminous efficacy of luminaires: 71 lm/W, Service life: 50000h at 85% luminous flux, with ballast unit, modular, high-quality optical unit made of reflector and LED light chamber, integrated in optimized heat management made of die-cast aluminum, smooth reflector coated in aluminium, matt, reflector/cover frame made of high-quality, UV-resistant polycarbonate (PC), white cover frame, mounting frame made of die-cast aluminum, tool-free quick assembly of the lighting unit via EASY-CLICK fastener, IP44_IP20, luminaire wired halogen-free, connection: 3-pin plug-in connection terminal, Dur Looping possible, mains voltage: 220-240V / 0/50/60Hz, suitable for central battery 220V DC, assembly: tool-free quick assembly using retaining springs for ceiling thicknesses of 1-25mm, ceiling cut-out: 100x100mm, installation depth: 102mm, weight: 0.64 kg, note: UGR

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

