

**LED ceiling/wall light 3000K D675H50dimDALI - Ceiling-  
/wall luminaire 1x54W 311845.000.76**



**RZB**

311845.000.76

4051859065043 EAN/GTIN

**973,72 GBP** excl. VAT\*\*

plus shipping bulky item



14-16 days\* (GBR)



LED ceiling/wall light 3000K D675H50dimDALI 311845.000.76 Suitable for wall mounting, Suitable for ceiling mounting, Suitable for surface mounting, Light source LED not interchangeable, With light source, Suitable for number of light sources 1, Other socket, Housing material aluminium, Housing color aluminium, Cover material Structured glass, design of the louvre without, voltage type AC, nominal voltage 230 ... 230V, control gear LED control gear current-controlled, with control gear, DALI dimming, dimming dependent on control gear, light distributor without, light distribution symmetrical, beam angle unshielded/diffuse, light emission direct, rated service life L70/B10 at 25 °C 50000h, degree of protection (IP) IP40, degree of protection (NEMA) other, impact resistance IK02, protection class I, rated ambient temperature according to IEC62722-2-1 25 ... 25°C, glow wire test according to IEC 60695-2-11 960 °C - 30 s, suitable for lamp power 54 ... 54W, max. system power 54W, rated luminous flux according to IEC 6272 2-2-1 3450lm, light color white, color temperature 3000 ... 3000K, color rendering index CRI 80-89, luminous efficacy of luminaire 64lm/W, power factor 0.98, height/depth 50mm, outer diameter 675mm, type of wiring termination, number of poles 5, conductor cross-section 2.5mm², connection type plug-in terminal, extensive series consisting of: pendant lights. ceiling lights. wall lights. Lateral light coupling with LED. Implementation of the latest LED technology in a minimalist design. An anodized extruded aluminum profile that is only 15 mm flat holds the diffuser. Design of the unmistakable surface light with an opal/prismatic plastic diffuser or with handcrafted FerroMurano glass panes in 4 color variants. Design of the unmistakable panel light structured by diffuser glass. Painted aluminum cover. Anodised aluminum frame. Diffuser handmade colored glass FerroMurano red. Built-in operating device. Lateral light coupling with LED. Bulbs (LED) included.

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

