×



Item Number EB15710656

https://www.eibabo.uk/doepke/rcd-combination-rcbo-earth-leakage-circuit-breaker-drcbo3-b16-0-3-1na-eb15710656



RCD combination/RCBO - Earth leakage circuit breaker DRCBO3 B16/0,3/1N-A

Doepke

DRCBO3 B16/0,3/1N-A 09932114 4014712220669 EAN/GTIN

43,07 GBP excl. VAT**

plus **shipping**



3-5 days* (GBR)

FI/LS combination/RCBO DRCBO3 B16/0.3/1N-A number of poles (total) 2, number of fused poles 1, rated voltage 230V, rated insulation voltage Ui 440V, rated impulse withstand voltage Uimp 4kV, rated current 16A, rated residual current 0.3A, residual current Type A, energy limitation class 3, rated breaking capacity according to EN 61009 10kA, rated breaking capacity according to IEC 60947-2 10kA, rated short-circuit breaking capacity Icn according to EN 61009-1 10kA, instantaneous switch-off characteristic, surge current strength 0.25kA, type of voltage AC, frequency 50 Hz, tripping characteristic B, overvoltage category 3, Pollution degree 2, ambient temperature during operation -25 ... 40°C, width in pitch units 2, installation depth 68mm, degree of protection (IP) IP20, connectable conductor cross-section solid 1 ... 25mm², connectable conductor crosssection stranded 1 ... 25mm², combine RCBO Residual current circuit breaker and miniature circuit breaker in one device (FI/LS combination). They protect people from fault currents and systems from short circuits and overloads. The switches of the DRCBO 3 series work independently of the mains voltage and are characterized by a high rated switching capacity. Separate displays enable a quick overview of the current operating status. DRCBO 3 can be easily installed and removed. Type A switches are pulse and AC sensitive. This function is independent of the mains voltage. Switches with tripping characteristic B are the standard protection for light and socket circuits. Standard switches are designed for circuits with a rated voltage of 230 V or 400 V and a rated frequency of 50 Hz. Properties: tripping independent of auxiliary voltage, sensitive to AC and pulsating DC residual currents (type A) small size for all rated currents, high short-circuit strength, green-red contact position indicator, residual current tripping indicator, clamping yoke terminals with protection from behind and wide terminal cross-section range for rail and cable wiring on both connection sides, neutral conductor on the right, tristable latching slide for easy installation and removal, type of installation: quick fastening on DIN rail, any installation position, any supply, areas of application: protection of circuits in residential and commercial buildings as well as industrial plants with TN-S and TN-CS networks. In IT networks, RCBOs can be provided to switch off in the event of a second earth fault. Use in systems with TN-C networks and to protect circuits is excluded. in which power electronics equipment can cause smooth DC fault currents or fault currents with...

YOUR ADVANTAGES



WORLDWIDE TRADE Corporate video eibmarkt®



COMPLAINTS HANDLING Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

