



Frequency converter 4kW, 380-480V ATV630U40N4



Schneider Electric
ATV630U40N4
 3606480758133 EAN/GTIN

783,49 GBP excl. VAT**
 plus shipping



14-16 days* (GBR)

Frequency converter 4kW, 380-480V ATV630U40N4 mains voltage 380... 480V, mains frequency 50/60 Hz, input phase number 3, output phase number 3, max. output frequency 500Hz, max. output voltage 480V, nominal output current I_{2N} 9.3A, max. output power with linear load at Rated output voltage 4kW, Relative symmetrical mains frequency tolerance 5%, With control element, Can be used in industrial areas, Can be used in residential and commercial areas, supports protocol for TCP/IP, supports protocol for PROFIBUS, supports protocol for MODBUS, supports protocol for DeviceNet, supports protocol for PROFINET IO, supports protocol for EtherNet/IP, number of HW interfaces Industrial Ethernet 1, number of interfaces PROFINET 0, number of HW interfaces serial RS-232 0, number of HW interfaces serial RS-422 0, number of HW - Interfaces serial RS-485 1, number of HW interfaces serial TTY 0, number of HW interfaces USB 0, number of HW Parallel interfaces 0, number of HW interfaces other 0, 4-quadrant operation possible, type of converter other, degree of protection (IP) IP21, height 350mm, width 144mm, depth 203mm, Altivar 600 process frequency converter - converter for operating and protecting pumps. Variable speed drive ATV630, 5 HP, 380-480V, IP21/UL type 1. Dimensions: 144 x 350 x 203 mm, power KW: 4 kW. Output frequency 0.1-500 Hz. Overload in normal operation 110% for 60s, overload in high overload mode 150% for 60s (when derating by one power class). Control types: asynchronous motors, constant torque, variable torque, optimized torque mode, PM synchronous motor, (permanent magnet) motor. Integrated safety function: STO (Safe Torque Off) SIL3. Number of onboard I/O: Analog inputs 3. Analog outputs 2. Digital inputs: 8. Relay outputs: 3. Onboard communications: Modbus/TCP, Modbus serial port. Configuration and operating elements: Decentralized graphic operator terminal, integrated web server, DTM (Device Type Manager), SoMove software. Optional: I/O expansion cards, relay output cards. Optional communication cards, (EtherNet/IP and Modbus/TCP with two ports, CANopen Daisy Chain RJ45, Sub-D and screw terminals, ProfiNet, Profibus DP V1 and DeviceNet).

YOUR ADVANTAGES



WORLDWIDE TRADE
 Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
 > 500,000 customers worldwide



DHL TRACK & TRACE
 Shipment tracking



COMPLAINTS HANDLING
 Obliging and 100% safely



25 YEARS OF EXPERIENCE
 In worldwide mail order



ORDER LIVE CHAT
 With order history



SHORT DELIVERY TIME
 Warehousing



REFUND
 Within 14 days



DATA PROTECTION
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
 eibabo® electronics cheap online order
 eibabo® electric appliances buy online

