



Mobile panel 4", touch 6AV2125-2DB23-0AX0


Siemens

6AV2125-2DB23-0AX0

4047623406747 EAN/GTIN

1050,06 GBP excl. VAT**
plus shipping



14-16 days* (GBR)

Mobile panel 4,3", Supply voltage for DC 19.2..28.8 V, Voltage type of the supply voltage DC, Number of HW interfaces, Industrial Ethernet 1, Number of interfaces PROFINET 1, Number of HW interfaces USB 1, Supports protocol for TCP/IP yes, Supports protocol for PROFIBUS no, Supports protocol for CAN no, Supports protocol for INTERBUS no, Supports protocol for ASI no, Supports protocol for KNX no, Supports protocol for MODBUS yes, Supports data highway protocol no, Supports protocol for DeviceNet no, Supports protocol for SUCONET no, Supports protocol for LON no, Supports protocol for PROFINET IO yes, Supports protocol for PROFINET CBA no, Supports protocol for SERCOS no, Supports protocol for Ethernet/IP yes, Supports protocol for DeviceNet Safety no, Supports protocol for INTERBUS safety no, Supports protocol for PROFIsafe yes, Supports protocol for SafetyBUS p no, Wireless standard Bluetooth no, Wireless standard WLAN 802.11 no, Wireless standard GPRS no, Wireless standard GSM no, Wireless standard UMTS no, IO link master no, Type of display TFT, With color display yes, Number of colors of the display 16777216, Screen size 4.3 inches, Number of pixels, horizontal 480, Number of pixels, vertical 272, With alpha keyboard no, Number of function keys, programmable 4, Number of buttons with LED 4, With enabling button / deadman button yes, With touch screen yes, With message display yes, With message system (including buffer and acknowledgment) yes, Process value representation (output) possible yes, Process value specification (input) possible yes, With recipes yes, Number of levels, password protection 50, With print output no, Number of online languages 32, Degree of protection (IP) IP65, Operating temperature 0..45 °C, Suitable for EMERGENCY STOP yes, Connection, pluggable yes, Max. height of fall, according to standard IEC 60068-2-32 1.2 m, Suitable for safety functions yes, Width 194 mm, Height 166 mm, Depth 87 mm, Weight 0.7 kg

YOUR ADVANTAGES



WORLDWIDE TRADE

Corporate video eibmarkt®



99% CUSTOMER SATISFACTION

> 500,000 customers worldwide



DHL TRACK & TRACE

Shipment tracking



COMPLAINTS HANDLING

Obliging and 100% safely



25 YEARS OF EXPERIENCE

In worldwide mail order



ORDER LIVE CHAT

With order history



SHORT DELIVERY TIME

Warehousing



REFUND

Within 14 days



DATA PROTECTION

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

