


Motion detector, 230 degrees, 12-24V, remote controlled RC 230i UC

ESYLUX
 RC 230i UC
 EM10015649
 4015120015649 EAN/GTIN

83,48 GBP excl. VAT**
 plus shipping


3-5 days* (GBR)

Motion detector 230 degrees 12-24V remotely controllable RC 230i UC Design motion detector, sensor type passive infrared, creep protection/rear field monitoring, scanning angle 230°, optimal mounting height 2.5m, stairwell monitoring, max. range to one side 20m, max. range frontally 8m, detection field diameter up floor 40m, remote controllable, response sensitivity adjustable, response brightness adjustable, teach function for response brightness, suitable for ceiling mounting, suitable for wall mounting, surface mounting type, connection type screw terminal, plastic material, thermoplastic material quality, surface untreated, surface design matt, color white, RAL Number (similar) 9010, degree of protection (IP) IP54, type of voltage AC/DC, frequency 50 ... 60Hz, nominal voltage 24V, min. switch-on time 15s, max. switch-on time 30min, switch-off delay 5s, switch-on delay 0s, horizontal detection angle 0 ... 230°, swivel range sensor, horizontal 0°, swivel range sensor, vertical 0°, response Brightness 2 ... 2500lx, max. switching capacity 36W, temperature -25 ... 55°C, number of switching zones 1, max long range. 360° creep-under protection for complete detection, can be switched off by remote control. Programmable by remote control, e.g. B. Permanent light ON/OFF and automatic read-in function of the current light value. Fixed factory program ensures immediate operational readiness. Easy programming via remote control with blue mode technology. Avoidance of operating errors through integrated selector switch for test function/remote control/potentiometer setting. One-hand socket assembly. Double membrane cable entry. Concealed terminal base with large wiring space. Range adjustment of the sensor with additional focus LED as an adjustment aid. Retractable adjustment elements prevent unintentional adjustment of the parameters. Wall or ceiling mounting is possible without accessories thanks to the swivel joint. Hide individual areas with the enclosed cover cap (can be cut to size). Special base for inside and outside corner mounting as an accessory.

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

DHL TRACK & TRACE
Shipment tracking

COMPLAINTS HANDLING
Obliging and 100% safely

25 YEARS OF EXPERIENCE
In worldwide mail order

ORDER LIVE CHAT
With order history

SHORT DELIVERY TIME
Warehousing

REFUND
Within 14 days

DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

