



Wall presence detector 180 degrees, 12-36V AC DC, white PD-C 180i/16 UC



ESYLUX
PD-C 180i/16 UC
EP10427305
4015120427305 EAN/GTIN

88,97 GBP excl. VAT**
plus shipping



3-5 days* (GBR)

Wall-mounted presence detector 180 degrees, UP, FB PD-C 180i/16 UC Presence detector version, sensor type passive infrared, constant light control, forced switch-on, forced switch-off, animal passage, creep-under protection/rear field monitoring, scanning angle 180°, optimal mounting height 1.1m, stairwell monitoring, max one side 8m, max. presence area 25.17m², max. frontal range 6m, detection field diameter on the floor 16m, remote controllable, response sensitivity adjustable, response brightness adjustable, with signal unit, teach function for response brightness, suitable for wall mounting, dimming function with dimming insert, flush-mounting type of installation, connection type plug-in terminal, material plastic, material quality thermoplastic, halogen-free, surface untreated, surface design matt, color other, RAL number (similar) 9010, protection class (IP) IP20, type of voltage AC/DC, frequency 50 ... 60Hz, nominal voltage 36V, min. duty cycle 60s, max. duty cycle 60min, switch-off delay 300s, switch-on delay 30s, horizontal detection angle 0 ... 180°, sensor swivel range, horizontal 0°, sensor swivel range, vertical 0°, response brightness 5 ... 2000lx, max. switching capacity 72W, temperature -25 ... 50°C, number of Switching zones 1, max. inrush current 2A, control current 0mA, extension input, width 70mm, height 55mm, depth 70mm, installation width 61mm, installation depth 34mm, installation length 61mm, installation diameter 60mm, min. depth of the device box 34mm, presence detector with 180° detection area for wall mounting. Range of up to 16m in diameter for use in conjunction with building automation systems. Operating voltage 12-36 V DC or AC (AC/DC). Potential-free software-controlled switching output (opener/closer). Detection display that can be switched on and off. Noiseless switching up to max. 2 A. Compatible with brand switches, IP 20 covers available in different colours. Additional button input for individual manual switching. Universal surface-mounted box IP 20/IP 44 with triple membrane cable entry.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

