

**LED wall light 4000K Up+Down - Ceiling-/wall luminaire
2x4W 582027.0031.1****RZB**

582027.0031.1

4051859228325 EAN/GTIN

171,36 GBP excl. VAT**

plus shipping



14-16 days* (GBR)

LED wall light 4000K Up+Down 582027.0031.1 Suitable for wall mounting, Suitable for surface mounting, LED illuminant cannot be replaced, With illuminant, Suitable for computer workstations according to EN 12464-1, Suitable for number of illuminants 2, Other socket, Housing material aluminium, Housing color anthracite, Material of the cover glass transparent, design of the louvre without, voltage type AC, nominal voltage 220 ... 240V, control gear not required, without dimming function, light distributor without, light distribution asymmetrical, beam angle unshielded/diffuse, light emission direct/indirect, protection class (IP) IP65, protection class (NEMA) other, impact resistance IK03, protection class I, rated ambient temperature according to IEC62722-2-1 -20 ... 40°C, glow wire test according to IEC 60695-2-11 960 °C - 30 s, suitable for lamp power 4 ... 4W, Max. system power 8W, rated luminous flux according to IEC 62722-2-1 290lm, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, lights luminous efficacy 37lm/W, width 154mm, height/depth 127mm, length 100mm, type of wiring termination, number of poles 3, conductor cross-section 2.5mm², connection type plug-in terminal, Made in Germany. The clear language of form supports applications in modern architecture. The soft light emission at the edge of the glass gives the lamp its unmistakable character. The innovative housing concept protects the light source and control gear from all weather conditions. Fast installation: wall mounting and electrical connection are only made on the wall plate, the lamp head is then attached without screws and held in place with a Gravalock. The standard large cable inlet allows for easy network forwarding without an additional junction box. Variant for LEDPAR16 lamps with GU10 base available. Housing made of corrosion-resistant die-cast aluminum for outdoor use, powder-coated. Cover clear safety glass (ESG) with side-glow effect, ceramic coated. With bayonet lock. Wall mounting outside the sealed area with bore tolerance compensation. Screwless lamp attachment using Gravalock. Light source (mains voltage LED module) included. Standard with diaphragm valve to prevent condensation. Electrical connection with plug-in connection terminals on the wall base with quick connector. With second cable inlet for network forwarding.

YOUR ADVANTAGES**WORLDWIDE TRADE**
Corporate video eibmarkt®**99% CUSTOMER SATISFACTION**
> 500,000 customers worldwide**DHL TRACK & TRACE**
Shipment tracking**COMPLAINTS HANDLING**
Obliging and 100% safely**25 YEARS OF EXPERIENCE**
In worldwide mail order**ORDER LIVE CHAT**
With order history**SHORT DELIVERY TIME**
Warehousing**REFUND**
Within 14 days**DATA PROTECTION**
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

