

**LED wall ceiling light 4000K - Ceiling-/wall luminaire
1x27W 312240.002.3**



RZB
312240.002.3
4051859234296 EAN/GTIN

155,30 GBP excl. VAT**
plus shipping



14-16 days* (GBR)

LED wall ceiling light 4000K 312240.002.3 Energy efficiency class of the supplied replaceable light source A+, Highest energy efficiency class of the replaceable light source A+, Lowest energy efficiency class of the replaceable light source A+, Energy efficiency class range A++ to E, Suitable for wall mounting, Suitable for ceiling mounting, Suitable for surface mounting, light source LED not interchangeable, with illuminant, suitable for number of illuminants 1, other socket, housing material steel, housing color white, cover material plastic opal, design of the grid without, type of voltage AC, nominal voltage 220 ... 240V, operating device not required, without dimming function, light distributor without, symmetrical light distribution, beam angle unshielded/diffuse, light emission direct/indirect, rated service life L70/B10 at 25 °C 50000h, rated service life L70/B50 at 25 °C 50000h, protection class (IP) IP40, protection class (NEMA) other, impact resistance IK03, Schutz zclass I, rated ambient temperature according to IEC62722-2-1 -20 ... 35°C, glow wire test according to IEC 60695-2-11 650 °C - 30 s, suitable for lamp power 27 ... 27W, max. system power 27W, rated luminous flux according to IEC 62722-2-1 2750lm, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, luminous efficacy of luminaire 102lm/W, height/depth 70mm, outer diameter 460mm, type of wiring termination, number of positions 3, conductor cross-section 2.5mm², Connection type plug-in terminal, completion of the extensive Flat Polymero® circle family with new flat diffusers. Homogeneous illumination through the use of LED surface modules. Extensive series consisting of: Pendant lights. ceiling lights. wall lights. Depending on the version, there is a choice of high-quality polycarbonate or acrylic glass (PMMA) for the lamp body. Various diameters available. With patented locking technology. Tool-free opening of the lamp. Replaceable LEDs. Light color 840. LED service life 50,000 h (L70, B10). Diffuser PMMA: stable, scratch-resistant (replacement for glass). UV-resistant (lightfast, no yellowing). absolutely weatherproof. Diffusor PC: hard, stiff, unbreakable, extremely impact-resistant. UV stabilized. Powder-coated metal bracket. Attachment of the cover with snap fastener. Cover plastic (PMMA) opal.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

