Item Number
EB16408260

29.03.2024/12:19

https://www.eibabo.uk/steinel/presence-detector-10m-ir-qu-hd-daliplus-de-eb16408260



Presence detector 10m IR QU HD DALIPLUS DE

Steinel
IR QU HD DALIPLUS DE
035204
4007841035204 EAN/GTIN

161,36 GBP excl. VAT**
plus **shipping**

14-16 days* (GBR)

Presence detector IR QU HD DALIPLUS DE Presence detector version, sensor type passive infrared, with DALI interface, constant light control, forced shutdown, creep under protection/rear field monitoring, networkable, optimal installation height 2.8m, bypass switch, max. range to one side 10m, max. presence area 8m², max Frontal range 10m, detection field diameter on the floor 8m, remote controllable, response brightness adjustable, with signal unit, teach function for response brightness, suitable for ceiling mounting, dimming function with dimming insert, mounting type other, connection type other, material plastic, material quality thermoplastic, halogen-free, surface other, Design of the surface matt, color white, RAL number (similar) 9010, protection class (IP) IP20, type of voltage AC, frequency 50 ... 60Hz, nominal voltage 240V, min. switch-on time 5s, max. switch-on time 60min, switch-off delay 300s, horizontal detection angle 360 ... 360°, response brightness 10 ... 1000lx, max 2000W, suitable for C-load, temperature 0 ... 40°C, number of switching zones 4800, max. inrush current 10A, min. inrush current 0.1A, control current 150mA, extension input, alarm function, width 120mm, height 124mm, depth 124mm , installation width 120mm, installation depth 124mm, installation length 120mm, entry into intelligent lighting control. Intelligent infrared presence detector IR Quattro HD DALI plus with extensive additional functions, ideal for classrooms, open-plan offices and car parks, installation height up to 10 m, with three light channels (DALI addressable) for up to 64 lights, easy to set up via app. Additional potential-free relay, constant light control and variable basic lighting functions, button interface for all 3 light channels for pressing and dimming as well as for the potential-free relay (light operation), remotely controllable via Smart Remote.

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

DHL TRACK & TRACE
Shipment tracking

COMPLAINTS HANDLING
Obliging and 100% safely

25 YEARS OF EXPERIENCE
In worldwide mail order

ORDER LIVE CHAT
With order history

SHORT DELIVERY TIME
Warehousing

REFUND
Within 14 days

DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).
** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online