



**LED street light 4000K - Luminaire for streets and places
R2L2 M 72L #96630711**



Zumtobel
R2L2 M 72L #96630711
96630711
5037319463474 EAN/GTIN

745,88 GBP excl. VAT**
plus shipping

 **14-16 days* (GBR)**

LED street light 4000K R2L2 M 72L 96630711 Light source LED not interchangeable, With light source, Suitable for number of light sources 1, Socket without, Housing material aluminium, Housing color grey, Cover material transparent glass, Type of voltage AC, Rated voltage 230 ... 230V, Control gear Current-controlled LED control gear, With control gear, Without dimming function, Energy efficiency class of the permanently installed lamp A++, A+, A (LED), Rated service life L70/B10 at 25 °C 100000h, Rated service life L70/B50 at 25 °C 100000h, Rated service life L80/B10 at 25 °C 100000h, Rated service life L80/B50 at 25 °C 100000h, Rated service life L90/B10 at 25 °C 100000h, Rated service life L90/B50 at 25 °C 100000h, Degree of protection (IP) IP66, Impact resistance IK08, Protection class I, Max. system power 75W, rated luminous flux according to IEC 62722-2-1 10717lm, light color white, color temperature 4000 ... 4000K, color rendering index CRI 70-79, power factor 0.95, width 370mm, height/d Depth 155mm, length 880mm, One LED street light, midi, with 72 LEDs, operated at 350mA, optics: narrow street. LED driver. Protection class I, IP66, IK08. Housing: Die-cast aluminium, light gray powder-coated, textured. Cover: glass, flat, tempered. Screws: stainless steel, with Ecolubric(R) treatment. Post-top mounting (diameter 60/76 mm, 0°/5°/10° tilt) or side-entry mounting (diameter 34/42/49/60 mm, 0°/-5°/-10°/-15° tilt). Equipped with 50% power reduction circuit, activated 3 hours before and 5 hours after a calculated midnight. Can be disabled at installation with an easily accessible internal switch or cable clamp. Including LED module with 4000K. Dimensions: 880 x 370 x 155 mm Luminaire power: 75 W Luminaire luminous flux: 12215 lm Luminaire efficacy: 163 lm/W Weight: 13.4 kg Windage area: 0.06 m²

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

