

**LED lamp L-TUBE-B 4000K 550mm Gen. F - LED-lamp/Multi-LED B22d white L-TUBE-B #0206681GF****Ridi-Leuchten**  
L-TUBE-B #0206681GF  
0206681GF  
4029299481303 EAN/GTIN**42,51 GBP** excl. VAT\*\*  
plus shipping

14-16 days\* (GBR)

LED lamp L-TUBE-B 4000K 550mm Gen. F L-TUBE-B 0206681GF Energy efficiency class A++, energy efficiency class spectrum A++ to E, nominal current 560 ... 560mA, lamp power 8 ... 8W, type of voltage DC, luminous flux 1400 ... 1400lm, rated luminous flux according to IEC 62722-2-1 1400lm, color rendering index CRI 80-89, lamp shape tube, double base, version glass/cover clear, light color according to EN 12464-1 neutral white 3300 to 5300 K, base B22d, color white, Light color 840 ... 840, color temperature 4000 ... 4000K, housing color white, color consistency (McAdam ellipse) SDCM3, dimmable, length 550mm, protection class (IP) IP20, weighted energy consumption in 1,000 hours 9kWh, average nominal service life 50000h, LED illuminant RIDI L-TUBE-B, color rendering Ra >= 80, color location tolerance < 3 Step Mac Adam (initial). LED modules designed as a linear circuit board. Mid-power LEDs for even illumination and maximum efficiency. Basic profile made of extruded solid aluminum for optimal thermal management. Linear plate twisted continuously over the entire length with the basic profile. Cover made of clear, frosted or opal PMMA for efficient light emission, end cover made of robust PC, colour-coordinated with the cover. Operation with an external LED driver (installed in the light), constant current, safety extra-low voltage of less than 60 volts (SELV-compliant). L-TUBE-B packaged. Length 550 mm, power consumption 8 watts. Color rendering Ra > 80. Light color 3000 (...830...), 4000 (...840...) or 6500 Kelvin (...865...). Installation: Factory installation in industrial and sports hall lights from the RIDI range. Tool-free, mechanical lamp replacement of the L-TUBE-B by releasing the snap-in connection of the spring steel clip on the connection side and shifting it on the long side and electrically via the socket-plug system.

**YOUR ADVANTAGES****WORLDWIDE TRADE**  
Corporate video eibmarkt®**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide**DHL TRACK & TRACE**  
Shipment tracking**COMPLAINTS HANDLING**  
Obliging and 100% safely**25 YEARS OF EXPERIENCE**  
In worldwide mail order**ORDER LIVE CHAT**  
With order history**SHORT DELIVERY TIME**  
Warehousing**REFUND**  
Within 14 days**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

**eibabo®** and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

**eibabo®** the Smart Home technology shop  
**eibabo®** electronics cheap online order  
**eibabo®** electric appliances buy online

