



Switch actuator heating cooling relay 4 channels - Heating actuator for home automation F4HK14



Eltako
F4HK14
30014010
4010312314982 EAN/GTIN

41,85 GBP excl. VAT**
plus shipping



3-5 days* (GBR)

Switch actuator heating cooling relay 4 channels F4HK14 radio bus system, other bus systems without, radio bidirectional, REG mounting type, width in modular units 1, with bus coupling, removable bus module, control variable constant, control variable switching, manual switching, number of binary inputs 0, max. switching current (resistive load) 4A, number of outputs 4, max. output current 4A, switching voltage 230 ... 230V, degree of protection (IP) IP20, heating/cooling relay with 4 channels, 1 NO contact each 4A/250V AC, isolated from the supply voltage, with DX Technology. Bidirectional. Standby loss only 0.1 watts. Connection to the Eltako RS485 bus. Bus cross-wiring and power supply with jumper. To do this, simply connect the N conductor to the terminal (N) and L to K(L). This results in an additional standby loss of only 0.1 watts. If all 4 relays are switched on, 0.7 watts are required. If the supply voltage fails, the system is switched off in a defined manner. This heating/cooling relay evaluates the information from wireless temperature controllers or sensors. Possibly supplemented by window-door contacts, motion detectors, window handle sensors FFG7B-rw and wireless pushbuttons. As an alternative to a wireless temperature controller, the temperature information about target and actual values can also be obtained from the GFVS software. There is also the option of specifying the target temperature via the GFVS software and thus limiting the setting range of the wireless temperature controller. Upper rotary switch for the adjustable hysteresis: left stop: smallest hysteresis 0.5 degrees. Center position: hysteresis 2.5 degrees. Right stop: largest hysteresis 4.5 degrees. In between, subdivision in 0.5 degree increments. Center rotary switch for the control modes. The LED under the upper rotary switch accompanies the teach-in process according to the operating instructions and indicates control commands during operation by flashing briefly.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

