



**LED moisture-proof light 4000K - Ceiling-/wall luminaire
AQFPRO S #96630753**



Zumtobel
AQFPRO S #96630753
96630753
5037319467649 EAN/GTIN

84,78 GBP excl. VAT**
plus shipping bulky item



3-5 days* (GBR)

LED moisture-proof luminaire 4000K AQFPRO S 96630753 Suitable for ceiling mounting, Suitable for surface mounting, LED bulbs cannot be replaced, With bulbs, Suitable for number of bulbs 1, Other socket, Housing material plastic, Housing color grey, Cover material plastic opal, Design of the grid without, Type of voltage AC, Rated voltage 220 ... 240V, Control gear LED control gear current-controlled, With control gear, Without dimming function, Light distribution symmetrical, Light emission direct, Rated service life L70/B50 at 25 °C 74000h, Rated service life L80/B50 at 25 °C 50000h, Rated service life L90/B50 at 25 °C 24000h, degree of protection (IP) IP66, impact resistance IK08, protection class I, luminaire with limited surface temperature "D mark", rated ambient temperature according to IEC62722-2-1 -20 ... 45°C, glow wire test according to IEC 60695-2-11 850 °C - 30 s, max. system power 22W, rated luminous flux according to IEC 62722-2-1 2900lm, light color white, color temperature 40 00 ... 4000K, color rendering index CRI 80-89, power factor 0.96, width 92mm, height/depth 90mm, length 1100mm, A dust and moisture resistant LED luminaire, IP66. Electronic, non-dimmable control gear. Light distribution: medium wide beam. Protection class I. Luminaire housing: polycarbonate (PC), light grey. Diffuser: polycarbonate (PC), opal, with high transmission and refraction prisms. Patented EasyClick mechanism for mounting the diffuser without clips. For surface or pendant mounting. Quick-release fasteners for surface mounting included. Suitable for ceiling or wall mounting (both vertically and horizontally). Sets for chain tension cable or support rail mounting are available as accessories. Suitable for through-wiring with H05VV or NYM cable (10A). Ambient temperature: -20°C to +45°C. Including LED module with 4000K... Note: Before specifying for use in ambient atmospheres with chemical stress, high or condensing humidity and large temperature fluctuations, please contact your consultant. Dimensions: 1100 x 92 x 90 mm Luminaire output: 21.7 W Luminaire luminous flux: 3130 lm Luminaire efficacy: 144 lm/W Weight: 1.7 kg

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

