

## Item Number EB12600650

https://www.eibabo.uk/fabas-luce/ceiling-light-2x60w-e27-glass-ws-surface-mounted-luminaire-2x60w-2385-65-102-eb12600650



## Ceiling light 2x60W E27 glass ws - Surface mounted luminaire 2x60W 2385-65-102

×

**Fabas Luce** 2385-65-102 8019282006534 EAN/GTIN

**33,33 GBP** excl. VAT\*\*

plus **shipping** 



3-5 days\* (GBR)

Ceiling light 2x60W E27 glass ws 2385-65-102, Suitable for wall mounting=yes, Suitable for pendant suspension=no, Suitable for ceiling mounting=yes, Suitable for recessed mounting=no, Suitable for surface mounting=yes, Light source=incandescent lamp, With light source=no, Suitable for continuous row configuration=no, suitable for VDU workstations according to EN 12464-1=no, suitable for number of lamps=2, socket=E27, housing material=steel, housing color=nickel, cover material=structured glass, grid design=none, type of voltage= AC, rated voltage=230 V, control gear=not required, with control gear=no, dimming 0-10 V=no, dimming 1-10 V=no, dimming DALI=no, dimming DMX=no, dimming DSI=no, dimming potentiometer (device-integrated)=no, dimming GPRS=no, dimming LineSwitch=no, dimming manufacturer-specific=no, dimming mains voltage modulation=no, dimming trailing edge=no, dimming leading edge=no, dimming programmable=no, dimming RF=no, dimming Sine Wave Red uction=no, touch and dim dimming=no, Zigbee dimming=no, dimming with push-button=no, dimming dependent on operating device=no, without dimming function=yes, light distributor=without, light distribution=asymmetrical, beam angle=unshielded/diffuse, Light emission=direct, degree of protection (IP)=IP20, degree of protection (NEMA)=2, protection class=I, luminaire with limited surface temperature "D mark"=no, rated ambient temperature according to IEC62722-2-1=-10..40 ° C, suitable for emergency light=no, with motion detector=no, with light sensor=no, the lamp can be covered with thermal insulation material=no, with air slots=no, glow wire test according to IEC 60695-2-11=none, suitable for lamp power=60 W, light color=other, width=130mm, height/depth=0mm, length=0mm, outer diameter=400mm, wiring type=termination, connection type=other, Fox, classic opal glass ceiling light - metal bracket"

## YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLING
Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- \*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- \*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

