

**LED moisture-proof light 5000K - Ceiling-/wall luminaire
111550460011****Lichtline**
111550460011
4260374013570 EAN/GTIN**110,13 GBP** excl. VAT**
plus shipping bulky item

3-5 days* (GBR)



LED moisture-proof luminaire 5000K 111550460011 Suitable for wall mounting, Suitable for pendulum suspension, Suitable for ceiling mounting, Luminous flux can be switched in stages, Suitable for surface mounting, LED bulbs cannot be replaced, With bulbs, Other socket, Housing material plastic, Housing color white, Cover material plastic opal, Design of the louvre without, Type of voltage AC/DC, Rated voltage 220 ... 240V, Control gear LED control gear, current-controlled, With control gear, Manufacturer-specific dimming, Light distributor diffuser lens/optics/panel, Light distribution symmetrical, Beam angle extremely wide >80°, Light emission direct, rated service life L80/B10 at 25 °C 50000h, degree of protection (IP) IP65, impact resistance IK08, protection class II, luminaire with limited surface temperature "D mark", rated ambient temperature according to IEC62722-2-1 -25 ... 50° C, Suitable for emergency lighting, Glow wire test according to IEC 60695-2-11 850 °C - 30 s, Max. system power 46W, Rated luminous flux according to IEC 62722-2-1 7000lm, light color white, color temperature 5000 ... 5000K, color rendering index CRI 80-89, luminous efficacy of luminaire 152lm/W, power factor 0.95, width 104mm, height/depth 57mm, length 1500mm, type of wiring with through-wiring, 5 poles, conductor cross-section 1.5mm², connection type plug-in terminal, LED moisture-proof light with through-wiring for indoor and outdoor use. Simple, quick installation on the wall or ceiling. Mounting brackets with anti-theft screw are included. Fastening possible over the entire length of the luminaire. Existing drill holes can be used for mounting. The power of the integrated ballast can be reduced with a DIP switch (100%, 75%, 50%). The smooth surface has a low tendency to get dirty and is easy to clean. The lamp is dust-proof, protected against water jets, impact-resistant up to 5J and UV-resistant. Pressure compensation element to protect against the formation of condensation in the event of temperature and pressure fluctuations. Long service life, high luminous flux, good color rendering, wide distribution. Particularly even light distribution thanks to the prismatic PC cover. Low maintenance. Energy savings of up to 60% compared to a conventional moisture-proof light. Unbreakable, suitable for use in IFS-certified areas.

YOUR ADVANTAGES**WORLDWIDE TRADE**
Corporate video eibmarkt®**99% CUSTOMER SATISFACTION**
> 500,000 customers worldwide**DHL TRACK & TRACE**
Shipment tracking**COMPLAINTS HANDLING**
Obliging and 100% safely**25 YEARS OF EXPERIENCE**
In worldwide mail order**ORDER LIVE CHAT**
With order history**SHORT DELIVERY TIME**
Warehousing**REFUND**
Within 14 days**DATA PROTECTION**
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

