



## KNX surface mounted presence detector mini, alpine white 6131/21-24



**Busch Jaeger**  
6131/21-24  
2CKA006132A0331  
4011395185773 EAN/GTIN

**104,74 GBP** excl. VAT\*\*  
plus shipping



3-5 days\* (GBR)

KNX surface-mounted presence detector alpine white mini Premi 6131/21-24 bus system KNX, presence detector design, surface-mounted installation, material plastic, material quality thermoplastic, surface untreated, surface design matt, color white, RAL number (similar) 9016, with bus coupling, extension input, creep-under protection/rear field monitoring, stairwell monitoring, adjustable response brightness, teach function for response brightness, optimum installation height 3m, detection field diameter on the floor 8m, number of channels 4, min. switch-on time 10s, max. switch-on time 1092min, min. depth of the device box 0mm, detection range (at 2.5 m, 3 m and 4 m mounting height): circular. Seated people Ø: max. 5 m, max. 6.5 m and max. 9 m. Walking people Ø: max. 6.5 m, max. 8 m and max. 10.5 m. Structure height 16 mm. With 4 channels. For dimming/regulating the brightness to a defined value in a designated detection area. HVAC function for controlling heating and/or cooling systems as well as ventilation systems in the designated detection area. Detector application with 2-stage switch-off function. Detector application with integrated monitoring function. Constant light controller with up to 2 independent channels. Constant light controller with max. 2 outputs for brightness-dependent dimming/control of two light strips in the room. Integrated object room temperature controller. 10 freely programmable IR channels (blue and/or white) including 5 logic channels (logic gate, gate, delay and staircase light). Evaluation via internal brightness sensor. Weighting of up to 2 external brightness values and the internal brightness sensor possible. The programming button can be activated with the IR hand-held transmitter 6010-25(-500). With integrated KNX bus coupler. Suitable for suspended ceilings with a panel thickness of 9 to 25 mm. Mounting hole dimension: Ø 68 mm. Suitable for surface mounting in combination with a AP housing. Does not fit in the British Standard and VDE flush-mounted box. Recommendation: HaloX-O flush-mounted box from Kaiser (item no. 1290-40) with the appropriate cover (1290-47 or 1290-85 for fair-faced concrete) or IBTronic H120-68 from Spelsberg (item no. 97600501).

### YOUR ADVANTAGES



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

