



KNX surface mounted presence detector Premium, alpine white 6131/31-24



Busch Jaeger
6131/31-24
2CKA006132A0335
4011395185810 EAN/GTIN

125,60 GBP excl. VAT**
plus shipping



3-5 days* (GBR)

KNX surface-mounted presence detector alpine white Premium 6131/31-24 KNX bus system, presence detector design, surface-mounted installation, material plastic, material quality thermoplastic, surface untreated, surface design matt, color white, RAL number (similar) 9016, with bus coupling, extension input, Creeping under protection/rear field monitoring, stairwell monitoring, response brightness adjustable, teach function for response brightness, optimum installation height 3m, detection field diameter on the floor 12m, number of channels 4, min. duty cycle 10s, max. duty cycle 1092min, min. depth of the device box 0mm, detection range (with 2.5m, 3m and 4m mounting height): circular. Seated people Ø: max. 8 m, max. 10 m and max. 14 m. Walking people Ø: max. 10 m, max. 12 m and max. 16 m. Structure height 23 mm. With 4 channels. For dimming/regulating the brightness to a defined value in a designated detection area. HVAC function for controlling heating and/or cooling systems as well as ventilation systems in the designated detection area. Detector application with 2-stage switch-off function. Detector application with integrated monitoring function. Constant light controller with up to 2 independent channels. Constant light controller with max. 2 outputs for brightness-dependent dimming/control of two light strips in the room. Integrated object room temperature controller. 10 freely programmable IR channels (blue and/or white) including 5 logic channels (logic gate, gate, delay and staircase light). Evaluation via internal brightness sensor. Weighting of up to 2 external brightness values and the internal brightness sensor possible. The programming button can be activated with the IR hand-held transmitter 6010-25(-500). With integrated KNX bus coupler. Suitable for suspended ceilings with a panel thickness of 9 to 25 mm. Mounting hole dimension: Ø 68 mm. Suitable for surface mounting in combination with a AP housing. Does not fit in the British Standard and VDE flush-mounted box. Recommendation: HaloX-O flush-mounted box from Kaiser (item no. 1290-40) with the appropriate cover (1290-47 or 1290-85 for fair-faced concrete) or IBTronic H120-68 from Spelsberg (item no. 97600501).

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

