KNX push button sensor 3 comfort 6-fold 513600

Gira
513600
4010337086871 EAN/GTIN

151,56 GBP excl. VAT**

plus **shipping**

🚚 **3-5 days* (GBR)**

KNX push-button sensor 3 comfort 6-fold 513600 bus system KNX, other bus systems without, type of installation flush-mounted, with theft/dismantling protection, number of actuation points 12, number of buttons 6, with LED display, material other, material quality other, surface other, version of Surface not applicable, other color, with room thermostat, protection class (IP) IP20, KNX push button sensor 3 comfort 6-fold (3+3) system 55 commissioning rocker Features: Installation on bus coupler 3. Dismantling protection by screwing. Two multicolored status LEDs per control surface. Integrated temperature sensor for measuring and forwarding the local room temperature. Rocker or button function can be set for each control surface. Rocker function: switching, dimming, shutter control, 1-byte value transmitter, 2-byte value transmitter, scene extension and room temperature controller extension. Button function: switching, dimming, shutter control, 1-byte value transmitter, 2-byte value transmitter, scene extension and room temperature controller extension. Controller extension: Operating mode changeover with normal and high priority, defined selection of an operating mode, changeover between different operating modes, change in presence status, setpoint shift. Blocking object for blocking individual button or rocker functions. Display of an alarm message by flashing all LEDs. Multicolored status LED (red, green, blue) is configurable globally or individually. A higher-level function can be activated via the bus, whereby the color and display information of individual status LEDs can be changed depending on the priority. Communication object for controlling the brightness of the status LED and for lighting the labeling field (e.g. to reduce the brightness in bedrooms at night). Labeling field lighting for rocker sets with labeling field. Labeling field lighting ON, OFF, automatic switch-off or switchable via object. Notes: Professional lettering via the Gira lettering service The push button sensor is supplied with a program-neutral commissioning rocker. The appropriate rocker set for the switch range must be ordered separately.

YOUR ADVANTAGES

▶ **WORLDWIDE TRADE** *Corporate video eibmarkt®*	✓ **99% CUSTOMER SATISFACTION** *> 500,000 customers worldwide*	✓ **DHL TRACK & TRACE** *Shipment tracking*
✓ **COMPLAINTS HANDLING** *Obliging and 100% safely*	✓ **25 YEARS OF EXPERIENCE** *In worldwide mail order*	✓ **ORDER LIVE CHAT** *With order history*
✓ **SHORT DELIVERY TIME** *Warehousing*	✓ **REFUND** *Within 14 days*	✓ **DATA PROTECTION** *Guarantee*

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online