

LED light line module DALI - Strip Light LED not exchangeable 722095750073



Lichtline
722095750073
4260374014317 EAN/GTIN

178,73 GBP excl. VAT**
plus shipping bulky item



3-5 days* (GBR)



LED light line module DALI 722095750073 Light source LED not interchangeable, With light source, Other socket, Material aluminium, Housing color aluminium, Type of voltage AC/DC, Rated voltage 220 ... 240V, Rated LED current at constant current 860 ... 860mA, Control gear LED control gear current-controlled, With control gear, Dimming DALI, Light distributor diffuser lens/optics/panel, Suitable for emergency lighting, Rated service life L80/B10 at 25 °C 50000h, Degree of protection (IP) IP54, Protection class I, Luminaire with limited surface temperature "D mark", glow wire test according to IEC 60695-2-11 850 °C - 30 s, suitable for lamp power 76 ... 76W, max. system power 76W, rated luminous flux according to IEC 62722-2-1 11500lm, light color white, color temperature 4000 ... 6500K, Color rendering index CRI 80-89, power factor 0.95, width 67mm, height/depth 47mm, length 2000mm, type of wiring with through-wiring, number of positions 7, conductor cross-section 1.5mm², connection type flat plug, electrical connection with plug-in system em, Color temperature can be switched in steps, Luminous flux can be switched in steps, Universally applicable LED light line module for indoor and protected outdoor areas. Quick and easy installation on a cable or chain or direct installation on the ceiling. Empty modules are available for empty fields. Connection with the ClickLUX ROCKET connection set. Control via DALI possible. The light color can be set using a slide switch (4000K, 5000K, 6500K), and the output can also be configured on the ballast (100%, 75%, 50%). The smooth surface has a low tendency to get dirty and is easy to clean. The lamp is dust and splash-proof. Suitable as a replacement for a conventional one or two-lamp T8/T5 trunking system. through wiring. Optimum light control through lens technology. High-quality aluminum housing. flicker free Mounting brackets are freely slidable along the length of the fixture. Long service life, high luminous flux, good color rendering. Particularly even light distribution. Low maintenance. Energy savings of up to 50% compared to a conventional light line system. Unbreakable, suitable for use in IFS-certified areas.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

