



## SIRIUS compact starter 0.1-0.4 A - Reversing starter combination 0,09kW 3RA6250-2AB32



**Siemens**  
**3RA6250-2AB32**  
 4011209714984 EAN/GTIN

**545,54 GBP** excl. VAT\*\*  
 plus shipping



14-16 days\* (GBR)

SIRIUS compact starter 0.1-0.4 A 3RA6250-2AB32 Type of motor starter Reversing starter, With short-circuit release, Rated control supply voltage  $U_s$  at AC 50 Hz 24 ... 24 V, Rated control supply voltage  $U_s$  at AC 60 Hz 24 ... 24 V, Rated control supply voltage  $U_s$  at DC 24 ... 24V, type of voltage for actuation AC/DC, rated operational power at AC-3, 400 V 0.09kW, rated operational current  $I_e$  0.4A, overload release current setting 0.1 ... 0.4A, number of auxiliary contacts as NO contact 2, number of the auxiliary contacts as NC contact 0, ambient temperature, upper limit without restrictions 40°C, tripping class adjustable, connection type main circuit spring-loaded connection, design of electrical connection for auxiliary and control circuit spring-loaded connection, type of coordination according to IEC 60947-4-3 class 2, number of indicator lights 3, protection class (IP) IP20, degree of protection (NEMA) others, width 90mm, height 191mm, depth 165mm, SIRIUS compact starter reversing starter 690 V AC/DC 24 V 50...60 Hz 0.1...0.4 A IP20 connection main current circuit: Spring-loaded connection Control circuit connection: Spring-loaded connection SIRIUS 3RA62 compact starter for direct starting of standard three-phase motors up to 32 A. The devices combine the functions of circuit breakers, contactors and electronic overload relays and have a very high level of operational reliability. A small variance simplifies the logistics. The compact design saves space in the control cabinet. Thanks to detachable clamps, easy replacement is possible. The devices are approved worldwide (eg IEC and UL/CSA). The compact starters are available as direct or reversing starters and are available with different setting ranges. Designed for AC/DC operation, they are available with screw-type spring-type terminals or without terminals. In addition to the communication connection via AS-Interface, the 3RA68 infeed system and auxiliary contacts and terminals are available as accessories. Simple, efficient, always up-to-date - the SIRIUS modular system .

### YOUR ADVANTAGES



**WORLDWIDE TRADE**  
 Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
 > 500,000 customers worldwide



**DHL TRACK & TRACE**  
 Shipment tracking



**COMPLAINTS HANDLING**  
 Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
 In worldwide mail order



**ORDER LIVE CHAT**  
 With order history



**SHORT DELIVERY TIME**  
 Warehousing



**REFUND**  
 Within 14 days



**DATA PROTECTION**  
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
 eibabo® electronics cheap online order  
 eibabo® electric appliances buy online

