

Item Number EB17006584

https://www.eibabo.uk/siemens/switch-disconnector-3ld3-iu-32a-safety-switch-3-p-3ld3248-0tk51-eb17 006584



Switch disconnector 3LD3 lu 32A - Safety switch 3-p 3LD3248-0TK51

×

Siemens

3LD3248-0TK51 4001869551012 EAN/GTIN

32,64 GBP excl. VAT**

plus **shipping**



14-16 days* (GBR)

Switch disconnector 3LD3 Iu 32A 3LD3248-0TK51 Version as main switch Version as maintenance/repair switch Version as safety switch Number of switches 1 Max. rated operational voltage Ue at AC 690V Rated uninterrupted current Iu 32A Rated uninterrupted current at AC-23, 400 V 22A at AC-21, 400 V 32A, rated operational power at AC-3, 400 V 9.5kW, rated short-time withstand current Icw 0.5kA, number of poles 3, number of auxiliary contacts as NC contacts 0, number of auxiliary contacts as changeover contacts 0, Device design Built-in device Fixed installation technology, Suitable for central front mounting, Suitable for distributor installation, Suitable for intermediate installation, Color of the actuating element black, Design of the actuating element short turning handle, Lockable, Connection type main circuit box terminal, Protection class (IP), front IP65, Protection class (NEMA) other, switch disconnector 3LD3, Iu 32 A main switch 3-pole rated operational power be i AC-23 A at 400V 11.5kW Floor mounting Basic switch with door coupling Central hole mounting 22.5mm Rotary drive black 66 x 66mm The 3LD main and emergency stop switch for safe disconnection of loads in a wide variety of environments. The possible uses of the 3LD3 line disconnectors are diverse. After disconnection from the mains, they ensure that all electrical equipment is safely isolated, switching, for example, three-phase motors, but also air conditioning and ventilation systems. 3LD3 are also predestined for the use of control or switching cabinets, especially for applications in small machines (e.g. saws, compressors, pumps, cement mixers, drills, milling machines and woodworking machines). The main features of the Siemens 3LD main and emergency stop switches are: 1. Modular design, quick and easy installation of auxiliary switches, N-PE terminal or 4th pole. 2. Versatile in use thanks to local approvals. 3. One mechanical size for five electrical sizes. 4. Can be used for direct current applications. 5. Types of mounting for the buildings

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION





25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

