

Item Number EB17008294

https://www.eibabo.uk/siemens/contactor-1nc-ac-110v-50hz-magnet-contactor-9a-110vac-3rt2016-4ak 62-eb17008294



Contactor 1NC, AC 110V 50Hz - Magnet contactor 9A 110VAC 3RT2016-4AK62

×

Siemens

3RT2016-4AK62 4011209844421 EAN/GTIN

24,23 GBP excl. VAT**

plus **shipping**



14-16 days* (GBR)

Contactor 1NC, AC 110V 50Hz 3RT2016-4AK62 Rated control supply voltage Us at AC 50 Hz 110 ... 110V, rated control supply voltage Us at AC 60 Hz 120 ... 120V, type of voltage for actuation AC, rated operational current le at AC-1, 400 V 22A, rated operational current le at AC-3, 400 V 9A, Rated operational power at AC-3, 400 V 4kW, Rated operational current le at AC-4, 400 V 8.5A, Rated operational power NEMA 3.67749375kW, Suitable for series installation, Number of auxiliary contacts as NC contacts 1, Connection type main circuit other, number of NO contacts as main contacts 3, power contactor, AC-3 9 A, 4 kW / 400 V 1 NC, AC 110 V, 50 Hz 120 V, 60 Hz, 3-pole, size S00, ring cable lug connection power contactor SIRIUS 3RT2 for switching motors. The 3RT2 contactors are part of the SIRIUS modular system with its perfectly matched products. They impress with their high performance combined with a compact design and high contact reliability. They can be combined with other components in the load feeder in a variety of ways. Many of the device combinations are tested at the factory. The contactors offer the optimal connection to the controller for every application (parallel, via ASi or IO-Link). Integrated auxiliary switches reduce the complexity of your structure. The front connections enable easy wiring. The 3RT2 contactors are climate-proof, approved worldwide (eg IEC and UL/CSA) and IE3/IE4ready. They are available in different sizes and in a large power range with AC and DC operation. In addition to screw connection technology, the devices are also consistently available with spring-loaded connections for a fast, maintenance-free and vibration-proof connection. The comprehensive range of accessories, such as auxiliary switches, auxiliary releases, etc., is the same for all sizes. The available link modules, function modules and the SIRIUS 3RV29 infeed system significantly reduce the amount of wiring. The 3RT2 power contactors replace the tried-and-tested 3RT1 series (up to 55 kW). Simple, efficient, always up-

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®




COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION





25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION *Guarantee*

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

