

## Item Number EB17006320

https://www.eibabo.uk/siemens/load-break-switch-3-pole-iu-25a-safety-switch-3-p-0-0095kw-3ld2115-0 tk53-eb17006320



Load-break switch 3-pole, lu: 25A - Safety switch 3-p 0,0095kW 3LD2115-0TK53

×

## Siemens

3LD2115-0TK53 4011209538498 EAN/GTIN

**39,51 GBP** excl. VAT\*\*

plus **shipping** 



14-16 days\* (GBR)

Switch-disconnector 3-pole, lu: 25A 3LD2115-0TK53 Design as a main switch Design as a maintenance/repair switch Design as a safety switch Design as a maintenance of the switch Design a STOP device Number of switches 1 Max. rated operational voltage Ue at AC 690V, rated uninterrupted current lu 25A, rated continuous current at AC-21, 400 V 25A, rated operational power at AC-3, 400 V 7.5kW, rated short-time withstand current lcw 0.64kA, rated operational power at AC-23, 400 V 0.0095kW, number of poles 3, number of auxiliary contacts as NC contacts 0, Number of auxiliary contacts as NO contacts as NO contacts as changeover contact 0, Device design built-in device, fixed installation, Suitable for 4-hole front attachment, Suitable for distributor installation, Suitable for intermediate installation, Color of the actuating element red, Design of the actuating element short rotary handle, Lockable, Main circuit connection type box terminal, degree of protection (IP), IP65 on the front, degree of protection (NEMA) other, SENTRON, switch disconnector 3LD, not -Off switch, 3-pin, lu: 25 A, operating power / at AC-23 A at 400V: 9.5 kW, floor mounting with door coupling, rotary drive, red/yellow, 4-hole mounting of the handle, without tolerance compensation The main and emergency stop switch 3LD as a repair switch for safe disconnection of loads in a wide variety of environments. The possible uses of the 3LD line disconnector are diverse. After disconnection from the mains, they ensure that all electrical equipment is safely isolated, switching, for example, three-phase motors, but also air conditioning and ventilation systems. 3LD have proven themselves in many areas, especially in machining and processing machines in machine and conveyor system construction, in the chemical or in the food and beverage industry. The main features of the Siemens 3LD main and emergency stop switches are: 1. Modular design, quick and easy installation of auxiliary switches, N-PE terminal or 4th pole. 2. Versatile and can be used worldwide thanks to international IEC, UL and shipbuilding approvals. 3. Degree of protection up to IP 65 with encapsulated housing for outdoor applications. 4. Can be used for direct current applications. 5. Types of mounting: front mounting, mounting plate, DIN rail. 6. Optimum mains separation from 16 A to 250 A thanks to the lockable rotary drive. Siemens offers an integrated portfolio of protection, switching, measuring and monitoring devices, distribution systems, switches and sockets for safe, efficient electrical infrastructure in buildings and industry.

## YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



**COMPLAINTS HANDLING**Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500.000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries

outside the EU.

\*\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

