


Item Number EB17006422

26.04.2024/13:09

×

https://www.eibabo.uk/siemens/load-break-switch-6-pole-250a-safety-switch-6-p-132kw-3ld2405-3vk13 -eb17006422



## Load-break switch 6-pole, 250A - Safety switch 6-p 132kW 3LD2405-3VK13

Siemens 3LD2405-3VK13 4011209768741 EAN/GTIN

## 567,95 GBP excl. VAT\*\*

plus **shipping** 

14-16 days\* (GBR)

Switch-disconnector 6-pole, 250A 3LD2405-3VK13 Version as a main switch Version as a maintenance/repair switch Version as a safety switch Version as an EMERGENCY STOP device Number of switches 1 Max. rated operational voltage Ue at AC 690V Rated uninterrupted current lu 250A Rated uninterrupted current at AC-23, 400 V 224A, rated uninterrupted current at AC-21, 400 V 250A, rated operational power at AC-3, 400 V 110kW, rated short-time withstand current lcw 4kA, rated operational power at AC-3, 400 V 132kW, number of poles 6, number of auxiliary contacts as NC contact 0, number of auxiliary contacts as changeover contact 0, device design built-in device fixed installation technology, suitable for 4-hole front attachment, color of the actuating element red, design of the actuating of the actuating lockable, connection type main circuit box terminal, degree of protection (IP), on the front IP65, degree of protection (NEMA) other, SENTRON, 3LD switch disconnector, emergency stop switch, 6-pin, Iu=2 50A, operating power / at AC-23 A at 400V: 132 kW, front-mounted, toggle drive, red/yellow, 4-hole attachment of the handle . The possible uses of the 3LD line disconnector are diverse. After disconnection from the mains, they ensure that all electrical equipment is safely isolated, switching, for example, three-phase motors, but also air conditioning and ventilation systems. 3LD have proven themselves in many areas, especially in machining and processing machines in machine and conveyor system construction, in the chemical or in the food and beverage industry. The main features of the Siemens 3LD main and emergency stop switches are: 1. Modular design, quick and easy installation of auxiliary switches, N-PE terminal or 4th pole. 2. Versatile and can be used worldwide thanks to international IEC UL and shipbuilding approvals. 3. Degree of protection up to IP 65 with encapsulated housing for outdoor applications. 4. Can be used for direct current applications. 5. Types of mounting; front mounting, mounting plate, DIN rail

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

