

Item Number EB17006689

×

https://www.eibabo.uk/siemens/switch-disconnector-3ld3-iu-63a-safety-switch-3-p-3ld3454-0tk53-eb17 006689

Switch disconnector 3LD3 lu 63A - Safety switch 3-p 3LD3454-0TK53

Siemens 3LD3454-0TK53 4001869552057 EAN/GTIN

32,48 GBP excl. VAT**

plus **shipping**

📕 14-16 days* (GBR)

Switch disconnector 3LD3 lu 63A 3LD3454-0TK53 Version as a main switch Version as a maintenance/repair switch Version as a safety switch Version as an EMERGENCY STOP device Number of switches 1 Max. rated operational voltage Ue at AC 690V Rated uninterrupted current lu 63A Rated uninterrupted current at AC -23, 400 V 43A, Rated uninterrupted current at AC-21, 400 V 63A, Rated operational power at AC-3, 400 V 18.5kW, Rated short-time withstand current lcw 1kA, Number of poles 3, Number of auxiliary contacts as NC contacts 0, Number of auxiliary contacts 0, Number of auxiliary contacts as NO contacts 0, Number of auxiliary contacts as NO contacts 0, Number of auxiliary contacts as NO contacts 0, Number of the actuating element red, design of the actuating element short rotary handle, lockable, connection type main circuit box terminal, degree of protection (IP), front IP65, degree of protection (NEMA) other, switch disconnector 3LD3, lu 63 A Main switch 3-pole Rated operational power at AC-23 A at 400V 22.0 k W Front mounting basic switch with central hole mounting 22.5 mm toggle drive red/yellow 66x66 mm The 3LD main and emergency stop switch for safe disconnection of loads in a wide variety of environments. The possible uses of the 3LD3 line disconnectors are diverse. After disconnection from the mains, they ensure that all electrical equipment is safely isolated, switching, for example, three-phase motors, but also air conditioning and ventilation systems. 3LD3 are also predestined for the use of control or switching cabinets, especially for applications in small machines (e.g. saws, compressors, pumps, cement mixers, drills, milling machines and woodworking machines). The main features of the Siemens 3LD main and emergency stop switches are: 1. Modular design, quick and easy installation of auxiliary switches, N-PE terminal or 4th pole. 2. Versatile in use thanks to local approvals. 3. One mechanical size for five electrical sizes. 4. Can be used for direct current applications. 5. Types of mounting; front mo

YOUR ADVANTAGES

SIE



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

