

Item Number EB17006693

×

https://www.eibabo.uk/siemens/switch-disconnector-3ld3-iu-63a-safety-switch-3-p-3ld3454-1tk53-eb17 006693

Switch disconnector 3LD3 lu 63A - Safety switch 3-p 3LD3454-1TK53

Siemens 3LD3454-1TK53 4001869552095 EAN/GTIN

39,57 GBP excl. VAT**

plus **shipping**



Switch disconnector 3LD3 lu 63A 3LD3454-1TK53 Design as a main switch Design as a maintenance/repair switch Design as a safety switch Design as an EMERGENCY STOP device Number of switches 1 Max. rated operational voltage Ue at AC 690V Rated uninterrupted current lu 63A Rated uninterrupted current at AC -23, 400 V 43A, Rated uninterrupted current at AC-21, 400 V 63A, Rated operational power at AC-3, 400 V 18.5kW, Rated short-time withstand current lcw 1kA, Number of poles 3, Number of auxiliary contacts as NC contacts 1, Number of auxiliary contacts as NO contacts 1, Number of poles 3, Number of installation technology, suitable for central front mounting, color of the actuating element red, design of the actuating element short rotary handle, lockable, connection type main circuit box terminal, degree of protection (IP), front IP65, degree of protection (NEMA) other, switch disconnector 3LD3, lu 63 A Main switch 3-pole Rated operational power at AC-23 A at 400V 22.0 k W Front mounting Basic switch with central hole mounting 22.5 mm toggle drive red/yellow 66x66 mm with auxiliary switch 10E+1S The 3LD main and emergency stop switch for safe disconnection of loads in a wide variety of environments. The possible uses of the 3LD3 line disconnectors are diverse. After disconnection from the mains, they ensure that all electrical equipment is safely isolated, switching, for example, three-phase motors, but also air conditioning and ventilation systems. 3LD3 are also predestined for the use of control or switching cabinets, especially for applications in small machines (e.g. saws, compressors, pumps, cement mixers, drills, milling machines and woodworking machines). The main features of the Siemens 3LD main and emergency stop switches are: 1. Modular design, quick and easy installation of auxiliary switches. N-PE terminal or 4th pole

YOUR ADVANTAGES

SIE



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

