

×

https://www.eibabo.uk/siemens/circuit-breaker-3va2-iec-frame-250-3va2225-5hl32-0ah0-eb17019843

Circuit breaker 3VA2 IEC Frame 250 3VA2225-5HL32-0AH0

Siemens

3VA2225-5HL32-0AH0 4042949027836 EAN/GTIN

854,72 GBP excl. VAT**

plus shipping



Circuit breaker 3VA2 IEC Frame 250 3VA2225-5HL32-0AH0 rated uninterrupted current lu 250A, rated voltage 690 ... 690V, rated limiting short-circuit breaking current lcu at 400 V, 50 Hz 55kA, overload release current setting 100 ... 250A, setting range of the instantaneous short-circuit release 375 ... 2500A, connection type Main circuit screw connection, device design built-in device fixed installation technology, suitable for top hat rail mounting, top hat rail mounting optional, number of auxiliary contacts as opener 0, number of auxiliary contacts as make contact 0, number of auxiliary contacts as changeover contact 3, with trip indicator, number of poles 3, position of the connection for the main circuit at the front, design of the Actuating element toggle lever, complete device with protection unit, optional motor drive, degree of protection (IP) IP40, circuit breaker 3VA2 IEC Frame 250 switching capacity class M Icu=55kA @ 415V 3-pole, system protection ETU320, LI, In=250A overload protection Ir=100A...250A short-circuit protection I = 1.5...10 x In screw flat connection 2 Hil fsbreaker HQ 1 Tripped signaling switch HQ 3VA2 molded case circuit breakers with ETU 3 series for system protection. The 3VA molded case circuit breakers from Siemens, as an important part of the SENTRON protective components for industrial applications and for applications in the infrastructure sector, offer effective starter and motor protection for systems through safe shutdown in the event of overload and short circuits. The 3VA molded case circuit breakers is primarily characterized by: 1. Compact design. 2. Available as a variant for system protection and generator protection depending on the ETU. 3. Available in 3 and 4 pole versions. 4. Depending on the size: rated current 25 A...630 A. 5. Four switching capacity classes from 55 kA ... 150 kA at 415 V. 6. Installation in permanent, plug-in technology, slide-in technology possible. 7. The series has an electronic overcurrent release. 8. Modular and easy to assemble internal

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL). ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries

outside the EU. *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

