Item Number
**EB17007647**

**28.03.2024/14:34**

https://www.eibabo.uk/siemens/auxiliary-contactor-for-railway-2no-2nc-dc24v-0.7-1.25-us-auxiliary-relay-24...34vdc-2nc-2-no...-eb17007647




## Auxiliary contactor for railway 2NO+2NC DC24V, 0.7-1.25*US - Auxiliary relay 24...34VDC 2NC/ 2 NO...

**Siemens**
3RH2122-2XB40-0LA2
4047621016139 EAN/GTIN

# 47,17 GBP excl. VAT**

plus **shipping**

14-16 days* (GBR)

Auxiliary contactor for railway 2S+2Ö DC24V, 0.7-1.25*US 3RH2122-2XB40-0LA2 Rated control supply voltage Us at DC 24 ... 34V, voltage type for actuation DC, rated operating current Ie, 400 V 3A, connection type auxiliary circuit spring-loaded connection, number of Auxiliary contacts as normally closed 2, number of auxiliary contacts as normally open 2, auxiliary contactor for railway 2S + 2Ö, DC 24-34V, 0.7...1.25*US, with integrated varistor size S00, spring-loaded connection suitable for PLC outputs auxiliary contactor railway SIRIUS 3RH2 for switching the control signals in the control circuit with strong fluctuations in the control voltages under extreme conditions, e.g. for railway applications. The SIRIUS 3RH2 contactor relays have standard-compliant connection designations and reliable, time-saving connection technology. By multiplying the output, it is possible to switch several auxiliary circuits at the same time. All contacts are also available as SUVA versions with forced guidance for safety applications. The auxiliary contactors are climate-proof, have high contact reliability and are suitable for worldwide use thanks to appropriate approvals (e.g. IEC and UL/CSA). This variant is characterized by an extended working and temperature range for harsher environmental conditions. They are available with AC or DC operation and are available with screw or spring-loaded technology. The basic version of the auxiliary contactors is 4-pole and can be expanded to 8 poles using snap-on auxiliary switches. The extensive accessories of the 3RT2 contactors for sizes S00 to S3 can also be used for the 3RH2 auxiliary contactors. The 3RH2 auxiliary contactors replace the proven 3RH1 series. Simple, efficient, always up to date - the SIRIUS modular system.

## YOUR ADVANTAGES

**WORLDWIDE TRADE**
*Corporate video eibmarkt®*

**99% CUSTOMER SATISFACTION**
*> 500,000 customers worldwide*

**DHL TRACK & TRACE**
*Shipment tracking*

**COMPLAINTS HANDLING**
*Obliging and 100% safely*

**25 YEARS OF EXPERIENCE**
*In worldwide mail order*

**ORDER LIVE CHAT**
*With order history*

**SHORT DELIVERY TIME**
*Warehousing*

**REFUND**
*Within 14 days*

**DATA PROTECTION**
*Guarantee*

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

**eibabo®** and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).
** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

**eibabo®** the Smart Home technology shop
**eibabo®** electronics cheap online order
**eibabo®** electric appliances buy online