

## Item Number EB17208786

https://www.eibabo.uk/ridi-leuchten/led-gear-tray-black-4000k-dali-gear-tray-for-light-line-system-1x50 w-vlgfp1501-1561008sw-eb17208786

## LED gear tray black, 4000K, DALI - Gear tray for light-line system 1x50W VLGFP1501 #1561008SW

×



VLGFP1501 #1561008SW 1561008SW 4029299508840 EAN/GTIN



plus **shipping bulky item** 



14-16 days\* (GBR)



LED gear tray black, 4000K, DALI VLGFP1501 1561008SW Light source LED not replaceable, With light source, Suitable for number of light sources 1, Housing material aluminium, Housing color black, Type of voltage AC, Nominal voltage 220 ... 240V, Control gear LED control gear current-controlled, With control gear, DALI dimming, reflector without, symmetrical light distribution, direct light emission, rated service life L80/B10 at 25 °C 65000h, rated service life L80/B50 at 25 °C 80000h, degree of protection (IP) IP54, protection class I, suitable for lamp power 50 ... 50W, Max. system power 55W, rated luminous flux according to IEC 62722-2-1 7710lm, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, width 67mm, height/depth 66mm, length 1500mm, LED gear tray made of aluminum profile, extruded, white (...WS-...) silver (...SI-...) or black (...SW-...) powder-coated. RIDI LED linear modules equipped with mid-power LEDs for maximum efficiency. The circuit boards are pressed onto the aluminum profile over their entire surface for optimal heat dissipation. Solder joints of the LED modules tested according to the strictest quality standard with regard to formation of cavities and stability with vibration and torsion. No thermal coupling between LED modules and converter. Linear optics with wide-angle light distribution made of clear, UV-resistant PMMA, integrated flush in the gear tray. End caps made of thermoplastic material for protection class up to IP54. Width of the gear tray identical to the mounting rail. Spring steel clip for fastening the gear tray in the VLTM trunking. Together with the VLTM trunking for the production of modular and variable light strips with protection class IP20 and IP54. The device mounts can be mounted anywhere on the trunking. Electrical adapter for flexible tapping of the power supply in the DIN rail with automatically contacted protective conductor. Phase selection by sliding contact. Color and optical coding for easy installation. Mechanical coding

## YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®




**COMPLAINTS HANDLING**Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION





25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

