

Item Number EB13256430

×

https://www.eibabo.uk/schuch/led-street-light-4000k-sk-ii-ip66-luminaire-for-streets-and-places-48l50va ri-480010703-eb13256430

## LED street light 4000K SK II IP66 - Luminaire for streets and places 48L50VARI#480010703

Schuch 48L50VARI#480010703 480010703 4041254320809 EAN/GTIN

## 297,96 GBP excl. VAT\*\*

plus shipping



LED street light 4000K SK II IP66 48L50VARI480010703 Type of mounting top/side-entry, bulbs LED not interchangeable, with bulbs, housing material aluminium, housing color silver, cover material glass transparent, type of voltage AC, nominal voltage 220... 240V, operating device LED Current-controlled control gear, with control gear, without dimming function, energy efficiency class of the built-in lamp A++, A+, A (LED), rated service life L80/B50 at 25 °C 100000h, protection class (IP) IP66, suitable for spigot size 42... 76mm, impact resistance IK08, protection class II, remote control without, max. system power 35W, rated luminous flux according to IEC 62722-2-1 4620lm, light color white, color temperature 4000... 4000K, color rendering index CRI 70-79, width 251mm, height/depth 155mm, length 610mm, LED -Street light with variably adjustable luminous flux. Two-part die-cast aluminum housing with smooth surface without external cooling fins, powder-coated metallic gray (DB 702N). Upper part with LED, optics, cover glass and electrical components, can be removed from the lower part for easy and time-saving installation. Lower part with integrated mast fastening system, cable entry, strain relief and pressure equalization system with internal ventilation in the mast connection area (protected against dirt). Inclination angle adjustment 0° to 10° for top mounting, 0° to -15° for side mounting depending on the inclination of the extension arm. Frameless, flat safety glass, impact resistance at least IK08. Disconnect plug connection and strain relief. High-performance LED with highly efficient optics modules, asymmetric wide beam light distribution, direct beam, multi-layer technology. Direct connection of the LED to the housing to ensure optimal thermal management. Electronic ballast, service life 100,000 hours, with overload, short-circuit and overtemperature protection class IP66. High-performance LED 4,000K, lifespan 100,000 hours (L80). Luminaire luminous flux adjustable to values between 2,510lm and 4,620lm,

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online



