



**LED wall light white - Ceiling-/wall luminaire 1x3,2W
232431**



SLV
232431
4024163148634 EAN/GTIN

57,24 GBP excl. VAT**
plus shipping



14-16 days* (GBR)

LED wall light white 232431, Suitable for wall mounting=yes, Suitable for pendant suspension=no, Suitable for ceiling mounting=no, Color temperature can be switched in steps=no, Suitable for recessed mounting=no, Luminous flux can be switched in steps=no, Suitable for surface mounting=yes, Illuminant=LED not interchangeable, with illuminant=yes, suitable for continuous row configuration=no, suitable for computer workstations according to EN 12464-1=no, suitable for number of illuminants=1, socket=other, housing material=aluminium, housing color=white, cover material= Glass transparent, design of the grid=none, type of voltage=AC, nominal voltage=100...277 V, control gear=LED control gear current-controlled, with control gear=yes, dimming 0-10 V=no, dimming 1-10 V=no, dimming DALI=no, DMX dimming=no, DSI dimming=no, potentiometer (device-integrated) dimming=no, GPRS dimming=no, LineSwitch dimming=no, manufacturer-specific dimming=no, mains voltage modulation dimming=no, phase cut-off dimming=no, Dimming phase control=no, dimming programmable=no, dimming RF=no, dimming Sine Wave Reduction=no, dimming Touch and Dim=no, dimming Zigbee=no, dimming with push-button=no, dimming dependent on operating device=no, none Dimming function=yes, light distributor=focus lens, light distribution=symmetrical, beam angle=extremely wide beam >80°, light emission=direct, type of protection (IP)=IP44, protection class=I, luminaire with limited surface temperature "D mark"=no, suitable for emergency light=no, with motion detector=no, with light sensor=no, the lamp can be covered with thermal insulation material=no, with air slots=no, suitable for lamp power=3.2 W, max. system power=4.5 W, rated luminous flux according to IEC 62722-2-1=290 lm, light color=white, color temperature=3000 K, color rendering index CRI=80-89, luminous efficacy=64 lm/W, width=84 mm, height/depth=110 mm, length=54 mm, Type of wiring=termination, The wall mounted with a powerful, warm white PowerLED uluminaire QUAD 1 XL is available in several color versions. The electrical connection of the light made of aluminum is made by the built-in driver to 230V mains voltage. Thanks to the protection class IP44, the light is suitable for outdoor use."

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

