Temperature controller pol-ws/gl time-controlled - Room thermostat 5 20462089

Berker
20462089
4011334502999 EAN/GTIN

160,48 GBP excl. VAT**
plus **shipping**

🚚 14-16 days* (GBR)

Temperature controller pol-ws/gl time-controlled 20462089 Version on/off, type of power supply 230 V AC, connection three/four-wire, measuring range lower value 5°C, measuring range upper value 30°C, control characteristic PI, heating, number of heating outputs 1 , number of cooling outputs 1, difference value 0.2 ... 0.2K, difference adjustable, temperature can be read, resistance sensor design, type of installation flush-mounted, with display, operation button, type contact closer, max. voltage of the contacts 230V, Max. contact load 10A, degree of protection (IP) IP20, color light white, RAL number 9010, height 71mm, width 71mm, depth 49.6mm, temperature controller class I, temperature controller time-controlled, Rx series 1930 polar white glossy. R.1 Program description Long text Switch program made of thermoplastic, unbreakable and impact-resistant, in the colors polar white (RAL 9010), black (RAL 9005), frame 1-way to 5-way, can be used vertically and horizontally. The socket center pieces and many other center pieces form an edgeless surface with the frame. Square basic shape and round corners 12 mm radius. With flat geometry and glossy surface. Round rockers/covers with a diameter of 58mm. Alternatively: switch range made from a 7 mm high thermoplastic carrier with a 3 mm glass surface on it, scratch-resistant, in the colors polar white (RAL 9010), black (RAL 9005), frame 1x to 5x, vertical like can be used horizontally. The socket center pieces and many other center pieces form an edgeless surface with the frame. Square basic shape and round corners 12 mm radius. With flat geometry and glossy surface. Round rockers/covers with a diameter of 58 mm. Alternatively: Switch range made from a 7 mm high thermoplastic carrier with a 3 mm metal surface on it made of stainless steel or aluminium, impact-resistant and unbreakable, frame 1-gang to 5-gang, can be used vertically and horizontally. The socket center pieces and many other center pieces form an edgeless surface with the frame. Square basic shape and round corners 12 mm radius. With flat geometry and glossy surface. Round rockers/covers with a diameter of 58 mm. Installation devices can be used in some cases with a separate sealing set that is water-protected UP IP 44. Possibility of labeling with frames that can be labeled, abrasion-resistant labeling of the products with printing. Can be illuminated according to workplace regulations. The material used is halogen-free and UV-stable, the surfaces are easy to clean and are resistant to disinfectants. Over 150 applications.

YOUR ADVANTAGES

▶ **WORLDWIDE TRADE**
Corporate video eibmarkt®

✓ **99% CUSTOMER SATISFACTION**
> 500,000 customers worldwide

✓ **DHL TRACK & TRACE**
Shipment tracking

✓ **COMPLAINTS HANDLING**
Obliging and 100% safely

✓ **25 YEARS OF EXPERIENCE**
In worldwide mail order

✓ **ORDER LIVE CHAT**
With order history

✓ **SHORT DELIVERY TIME**
Warehousing

✓ **REFUND**
Within 14 days

✓ **DATA PROTECTION**
Guarantee

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online