

Item Number EB17704767

20.04.2024/15:45

https://www.eibabo.uk/phoenix/pcb-connector-12a-320v-2-pin-gn-cable-connector-for-printed-circuit-fkc -2-5-8-1774768-eb17704767

## PCB connector 12A,320V,2-pin,gn - Cable connector for printed circuit FKC 2,5/8- #1774768

Phoenix FKC 2,5/8- #1774768 1774768 4046356481168 EAN/GTIN

## 177,30 GBP excl. VAT\*\*

plus shipping



Cable connector for printed circuit Type of connection Printed circuit board to cable, Contact type Socket, Number of poles 2, Number of plug-in contact rows 1, Modular spacing contacts 5,08mm, Modular spacing connections 5,08mm, Rated current In 12A, Rated voltage 320V, Rated surge voltage 4kV, Over voltage category III, Pollution degree 2, Connectable conductor cross section fine-strand without cable end sleeve 0,2 ... 2,5mm<sup>2</sup>, Connectable conductor cross section fine-strand without cable end sleeve 0,2 ... 2,5mm<sup>2</sup>, Connectable conductor cross section solid-core 0,2 ... 2,5mm<sup>2</sup>, Connectable conductor cross section fine-strand without cable end sleeve 0,2 ... 2,5mm<sup>2</sup>, Connectable conductor cross section fine-strand without cable end sleeve 0,2 ... 2,5mm<sup>2</sup>, Connectable conductor cross section fine-strand without cable end sleeve 0,2 ... 2,5mm<sup>2</sup>, Connectable conductor cross section fine-strand without cable end sleeve 0,2 ... 2,5mm<sup>2</sup>, Connectable conductor cross section fine-strand without cable end sleeve 0,2 ... 2,5mm<sup>2</sup>, Connectable conductor cross section fine-strand without cable end sleeve 0,2 ... 2,5mm<sup>2</sup>, Connectable conductor cross section fine-strand with cable end sleeve 0,2 ... 2,5mm<sup>2</sup>, Connectable conductor cross section multi-wired 0,2 ... 2,5mm<sup>2</sup>, Type of electric connection Other, Connectable cable type Tubular cable, Material of contact surface Tin, Material contact Copper, Material insulation body Other, Material housing Other, Coating housing Tinned, Colour housing Green, Inflammability class of insulation material acc. with UL94 V0, Operation temperature -40 ... -40°C

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.


\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online





×